

BLM		
Land Office		
H of M		
Operator		

Submit 3 Copies to Appropriate District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89
dist
up

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-015-26334
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Sidewinder
8. Well No. 1
9. Pool name or Wildcat Und. Crooked Creek (Morrow)

OCT 15 '90

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well Gas Well OTHER

2. Name of Operator
Yates Energy Corporation

3. Address of Operator
P. O. Box 2323, Roswell, NM 88202-2323

4. Well Location

Unit Letter F : 2310 Feet From The North Line and 1980 Feet From The West Line
Section 20 Township 24-S Range 24-E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4277.6 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Perforate & Treatment <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/9/90 Went in hole w/4 3/4" bit to PBD 3434' KB. Circ. 150 gals. Xylene followed by 200 gals. 15% HCL acid to btm. of tbg., reversed to pit to clean tbg. Pulled up hole to 3336' KB, displaced hole w/75 bbls. 2% KCL wtr. and spotted 250 gal. 10% acetic acid containing 1 gal. PENN 88. Ran CB-PDC log from 3440' - 1900', top of cement @ 2002' KB; good bond throughout with pressure on csg. Perforated w/4.0" Hyper III gun, top down, w/1 shot @ 3323', 3325', 3333', and 3335'.

7/10/90 Went in hole w/Baker Lok-set packer, four foot sub, "on-off" tool with 2.25" profile and balance of tbg. to 3,235' KB. Rev. circulated w/6 bbls. 2% KCL wtr. Spaced out and set packer @ 3235', installed a 2.5" full opening 5000 psig gate valve on tbg. Displaced acid w/8 bbls. 2% KCL wtr. open well to pit. Rig up to swab.

7/11/90 Acidized w/1200 gals. Moroflo, displaced w/21 bbls. 2% KCL wtr. Swabbing.

7/12/90 Fraced w/4000 gals. 50# gelled 2% KCL wtr. and 6000# 12/20 sand. Swabbing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sharon R. Hamilton TITLE Landman DATE 10/11/90

TYPE OR PRINT NAME Sharon R. Hamilton TELEPHONE NO. (505) 623-4935

(This space for State Use) ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE OCT 30 1990

CONDITIONS OF APPROVAL, IF ANY: