

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1004 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

OCT 15 '90

WELL API NO. 30-015-26334
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Sidewinder
8. Well No. 1
9. Pool name or Wildcat Und. Crooked Creek (Morrow)

SUNDRY NOTICES AND REPORTS ON WELLS O. C. D.
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
Yates Energy Corporation

3. Address of Operator
P. O. Box 2323, Roswell, NM 88202-2323

4. Well Location
Unit Letter F : 2310 Feet From The North Line and 1980 Feet From The West Line

Section 20 Township 24-S Range 24-E NMPM Eddy County
10. Elevation (Show whether DT, RAB, RT, GR, etc.)
4277.6 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Perforate and treatment <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/16/90 Loaded hole w/2% KCL wtr., released pkr. and reversed hole w/60 bbls. 2% KCL wtr. and spotted 250 gals. 10% acetic acid. POOH w/tbg. to pkr. Set CIBP @ 3318' KB. Pressured csg. to 2000 psig, OK. Perforated w/1 shot per interval @ 3280', 3282', 3284', 3286', 3288' and 3290'. (6 shots) w/Hyperjet III gun. Went in hole w/Baker Lok-set pkr., four foot sub, "on-off" tool w/2.25" profile, and 97 jts. tubing to 3201' KB. Reverse circulated w/6 bbls. 2% KCL wtr. Spaced out and set pkr. @ 3201' KB., installed a 2.25" full opening 5000 psig gate valve on tbg. Displaced acid w/11 bbls. 2% KCL wtr. Rig up to swab.

7/17/90 Acidized perforations w/1500 gals. 7.5% Moroflow acid containing 3.0 gals. PENN 88, displaced acid w/11 bbls. 2% KCL wtr. Swabbing.

7/19/90 Frac w/15,000 gals. 70 quality Methanol Foam (50/50), 25,000# 20/40 Brady sand and 8,000# 12/20 Brady Sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sharon R. Hamilton TITLE Landman DATE 10/11/90
TYPE OR PRINT NAME Sharon R. Hamilton TELEPHONE NO. (505) 623-4935

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE OCT 30 1990

CONDITIONS OF APPROVAL, IF ANY: