

YATES ENERGY CORPORATION
P.O. BOX 2323
ROSWELL, NEW MEXICO 88202-2323
(505)623-4935

SIDEWINDER #1
2310' FNL & 1980' FWL
SECTION 20-24S-24E
EDDY COUNTY, NEW MEXICO

31. Perforation Record

3323', 3325', 3333', 3335' 4.0" 1spf 4 holes
3280', 3282', 3284', 3286', 3288', 3290' 4.0" 1 spf 6 holes
2930', 2923' (3) 3/16" jets

32. Acid, Shot, Fracture, etc.

3323' - 3335' Treated w/250 gals 10% Acetic Acid. Acidized w/1200 gals.
7.5% Moroflo Acid. Fraced w/4000 gals. 50# gelled 2% KCL
wtr. and 6000# 12/20 sand.

3280' - 3290' Treated w/250 gals. 10% Acetic Acid. Acidized w/1500 gals.
7.5% Moroflo Acid. Fraced w/15,000 gals. 70 Quality Methanol
Foam (50/50) and 25,000# 20/40 Brady sand and 8000# 12/20
Brady sand.

2930' & 2923' Each jetted w/sand followed w/200 gals. 15% NEFE Acid.
Treated w/600 gals. 15% NEFE acid. Fraced w/10,000 gals. 70
quality 50/50 Methanol Foam w/15,000# 20/40 sand and 6000#
12/20 sand.