

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-36382
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-120

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line  
Section 16 Township 23S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3345' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-12-90. Spudded 26" hole 11:00 AM 6-12-90. Set 40' of 20" conductor. Cemented to surface. Notified NMOCD, Artesia, NM. Resumed drilling 17½" hole with rotary 8:00 AM 6-14-90. Ran 17 joints 13-3/8" 54.5# J-55 ST&C casing, set at 675'. Guide shoe set 675', insert float set at 632'. Cemented w/500 sx Class C with 2% CaCl + 4% gel (yield 1.67, wt 13.66). Tailed in w/300 sx Class C with 2% CaCl (yield 1.32, wt 14.8). PD 6:15 AM 6-15-90. Bumped plug to 650 psi, held okay. Circulated 255 sx cement. WOC. Drilled out 12:15 AM 6-16-90. WOC 18 hrs. Cut off and nipped up hydril and rotating head. Reduced hole to 12½" and resumed drilling.

NOTE: Pressure tested to 1800 psi for 30 minutes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 6-19-90

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY TITLE DATE  
CONDITIONS OF APPROVAL, IF ANY: