

- H. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations.

## 8. ANCILLARY FACILITIES

- A. None required.

## 9. WELLSITE LAYOUT

- A. **Exhibit C** shows the dimensions of the well pad and reserve pits, and the location of major rig components. The drilling contractor has not been selected and pad will be no larger than that shown. A new rig plat will be submitted as a sundry notice.
- B. The ground surface at the drilling location is sloping down slightly toward the southwest at 0.4 degree. No cut will be required to level and pad area, which will be covered with at least 4 to 6 inches of compacted caliche.
- C. The reserve pits will be plastic lined.
- D. The 400' x 400' pad and pit area has been staked and flagged.

## 10. PLANS FOR RESTORATION OF THE SURFACE

- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleared of all trash and junk, to leave the wellsite in as aesthetically pleasing a condition as possible.
- B. Unguarded pits, if any, containing fluids will be fenced until they have been filled.
- C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the Bureau of Land Management will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment or when dry.

## 11. OTHER INFORMATION

- A. **Topography:** The proposed location and road will be situated on a gently sloping due east of Dark Canyon. Surficial deposits, dominated by the clay and silt separates, are made up of compacted silt loams, silty clay loams and clay loams. Drainage is by sheetwash with runoff being to the east. Ground elevation is 3358.9'.
- B. **Soil:** The top soil at the wellsite is composed of typic calciorthid subgroups. Limestone cobbles and gravels are present on a recurrent basis.