

# PHILLIPS CASING AND TUBING, INC.

CASING DESIGN FOR: Pogo Producing Company  
Federal 23 No. 3

SIZE 13-3/8 - 5-1/2 DEPTH                      LOCATION                       
 MUD WEIGHT 10.0 #/gal .519 psi/ft.                      DESIGN FACTORS: COLLAPSE 1.125 BURST 1.1 TENSION 1.7

DESCRIPTION	SETTING DEPTH	SECTION LENGTH	CUMULATIVE WEIGHT	TENSION (1)			COLLAPSE (2)			BURST			COST
				STRENGTH 1000	DESIGN FACTOR	DESIGN FACTOR	FORCE	STRENGTH	DESIGN FACTOR	FORCE	STRENGTH	DESIGN FACTOR	
13-3/8 54.5 K-55 ST&C	840'	840	45,780	547	HI	436	1130	2.60	436	2730	HI		
8-5/8 32 J-55 ST&C			132,800	402	3.02	519	2530	HI	519	3930	HI		
8-5/8 24 J-55 ST&C	2300'	1300	100,800	263	2.60	1193	1370	1.14	1193	2950	2.47		
8-5/8 32 J-55 ST&C	4300'	2000	69,600	402	HI	2231	2530	1.13	2231	3930	1.76		
8-5/8 28 S-80 ST&C	4500'	200	5,600	414	HI	2335	3390	1.45	2335	2680	1.14		
5-1/2 17 K-55 LT&C	1000'	1000	137,000	272	1.98	--	4910	HI	--	5320	HI		
5-1/2 15.5 K-55 ST&C	6000'	5000	120,000	222	1.85	3114	4040	1.29	3114	4810	1.54		
5-1/2 17 N-80 LT&C	8500'	2500	42,500	348	HI	4411	6280	1.42	4411	7740	1.75		
2-7/8 6.5 N-80 EUE	8500'	8500	55,250	145	2.62	5000	11,160	2.23	5000	10,570	2.11	overpull 89,710	

**DESIGN CONDITIONS**

- (1) BOUYANCY ~~IS~~ NOT CONSIDERED.
- (2) TENSION EFFECT ON COLLAPSE RESISTANCE ~~IS~~ NOT CONSIDERED
- (3) FREIGHT ESTIMATED USING THEORETICAL WEIGHT AND APPROXIMATE MILEAGE

TOTAL COST FOB \_\_\_\_\_

FREIGHT (3) \_\_\_\_\_

TOTAL COST \_\_\_\_\_

Prepared by: *Richard L. Wright* Date 5-2-90

NOTE: The above design is furnished for informational purposes only.