(No	m 3160-5 vember 1983) rmerly 9-331)	UNIT. STAT DEPARTMENT OF THE BUREAU OF LAND MAN	E INTERIOR	SUBMIT IN TRIPLIC. Other instructions on referee sade ECEIVED	5. LEASE DESIGNATION AND SERIAL NO.
` ; ¯	SUND (Do not use this for	RY NOTICES AND RE rm for proposals to drill or to dee Use "APPLICATION FOR PERMIT-	PORTS ON V	WELLS a different reservoir.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME
1.	OIL GAS X	OTHER	CAR	KECFIAED	C. ONLI AGREEMENT NAME
2.	NAME OF OPERATOR	/		1228\$	8. FARM OR LEASE NAME
3.	ADDRESS OF OPERATOR	Gas Company V	20702	SEP 6'90	Federal 24 Com.
4.	P. U. BOX Z. LOCATION OF WELL (Rep See also apper 17 below At surface	267, Midland, Texas 7 Nort location clearly and in accorda	Oce with any State r	equirements. C. D. ARTESIA, OFFICE	10. FIELD AND POOL, OR WILDCAT Willow Lake (Atoka) 11. SEC., T., E., M., OR BLE, AND
	710' FNL &	2210' FWL			SURVEY OR AREA
14.	PERMIT NO.	15. ELEVATIONS (Sh	now whether DF, RT, GR,	, etc.)	Sec. 24, T24S, R28E 12. COUNTY OR PARISH 13. STATE
		2968.7'	_GR		Eddy NM
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data				
	NOTICE OF INTENTION TO:			QUBNT REPORT OF:	
	TEST WATER SHUT-OFF FRACTURE TREAT SHOOT CO ACIDIZE	PULL OR ALTER CASIN MULTIPLE COMPLETE ABANDON®	e —	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CANING ABANDONMENT*
	REPAIR WELL (Other)	CHANGE PLANS		(Norg: Report resul	St & cement job X X
		- Spud 11:30 am.	II	TOC D 40# W FF D	UCAO CTRC anaims
	10-14-90	- Set 607' of 13-3/8' Cemented with 575 s Tail with 200 sx C	sx 35:65 poz	"C" w/6% gel +	2% CaCl2 + 1/4# celloflake.
		WOC - 18-3/4 hours	; 1/4 hr pre	ssure tested to	500 psi, OK.
	10-20-90 - Set 2600' of 9-5/8" 36# K55 LT&C casing. Cemented with 1100 sx 35:65 poz "C" with 6% gel, 10% salt, 1/4# celloflake				
		Tail with 350 sx C	1 "C" with 2	% CaCl2. Circul	ated 207 sacks.
	WOC - 30 hours; 1/2 hour pressure tested to 2000#, OK.				
					Ad
					.:
17.	SIGNED ROTTY	he forefolgs is true and correct	TITLE Regul	atory Analyst	DATE 10/30/90
		<u> </u>			

*See Instructions on Reverse Side