

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐  
2. NAME OF OPERATOR  
RB Operating Company  
3. ADDRESS OF OPERATOR  
2412 N. Grandview, Suite 201, Odessa, TX 79761  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1651' FEL & 860 FNL Sec. 11-23S-28E  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☐  
(other) Drill & Set casing

5. LEASE  
NM32636  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Amoco "11" Federal  
9. WELL NO.  
6  
10. FIELD OR WILDCAT NAME  
E. Loving (Delaware)  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 11 - T23S - R28E  
12. COUNTY OR PARISH  
Eddy  
13. STATE  
NM  
14. API NO.  
30-015-26494  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3036.7 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/5/90 Spudded @ 3:30 P.M. Drilled to 543'. Ran 8-5/8" 24# K-55 casing set @ 543'. Cemented w/350 sx Class "C". Circulated 100 sx to pit.  
10/14/90 Reached total depth of 6370'. Ran DLL-GR-CAL from TD to surface FDL-CNL-CAL from TD to 4300'.  
10/15/90 Ran 5-1/2" - 15.50# J-55 and set @ 6369' w/DV @ 3510' cemented 1st stage w/450 sx 50/50 Poz "C" tailed in w/200 sx Class "C". Open DV. Cemented 2nd stage w/700 sx 35/65 Poz "C" tailed w/100 sx Class "C". Released rig @ 11:00 P.M. 10/15/90.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Sr. Prod. Engr. DATE 11/6/90

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: