

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR  
RB Operating Company

3. ADDRESS OF OPERATOR  
2412 N. Grandview, Suite 201, Odessa, Tx. 79761

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 910' FEL & 860' FSL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

(other) Casing & Cementing

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/27/90 Spudded @ 12:30 P.M. Drilled to 585'. Ran 8-5/8" 24# J-55 and set @ 585'. Cemented with 350 sx. Class "C". Ran temp survey-TOC @ 210'. Ran 1" and cemented with 225 sx. Cemented to surface.  
11/5/90 Drilled to TD of 6300'. Ran DLL-CML-CAL, FDC-CNL-CAL, & Frac height.  
11/6/90 Ran 5-1/2" 15.50# K-55 and set @ 6300'. D.V. tool @ 3485'. Cemented 1st stage with 500 sx 50/50 Poz "C" + 200 sx Class "C". 2nd. stage 850 sx. 35/65 Poz "C" + 100 sx Class "C". Released rig-W.O. completion unit.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James G. Shuford TITLE Sr. Prod. Engr. DATE November 9, 1990

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE 11/29/90