



CASING REPORT

RECEIVED

SURFACE ☐INTERMEDIATE ☒PRODUCTION ☐LINER ☐MAY 16 1991 12 / 5 / 90
MONTH DAY YEARLEASE NAME & WELL NO. PEOC '15' STATE No. 1O. C. D.
ARTESIA, OFFICEHOLE DATA: DRLD. SIZE 12 1/4" in. TO 2827 FTKB; REAMED SIZE in. TO FTKBCASING: SIZE 8 5/8 in. OD; TOTAL LENGTH 2840.76 FT.; JTS. 68 LANDED AT 2827 FTKB

DESCRIPTION (BOTTOM SEGMENT TO TOP SEGMENT)

LENGTH FEET	NUMBER OF JTS.	WEIGHT LBS./FT.	GRADE	THREAD	JOINT	CONDITION
<u>1.35</u>	<u>1</u>	<u>HALLIBURTON</u>	<u>Float Shoe</u>			
<u>42.08</u>	<u>1</u>	<u>32#</u>	<u>J-55</u>	<u>8rd</u>	<u>ST+C</u>	
<u>.92</u>	<u>1</u>	<u>HALLIBURTON</u>	<u>Float Collar</u>			
<u>2798.68</u>	<u>67</u>	<u>32</u>	<u>J-55</u>	<u>8rd</u>	<u>ST+C</u>	

CEMENT: CEMENTED WITH 1250 SX. OF Premium Plus HLC Cement w/ 6% Gel and 10# SALT. 2.01 cu ft/sx 12.8#/gal Followed by 150 sx Premium Plus Cement 1.32 cu ft/sx 14.8#/gal. Circ 334 sx Cement.

OBTAINED (FULL) (PARTIAL) (NO) MUD RETURNS. CEMENT (WAS) (WAS NOT) CIRC. TO SURFACE
BUMPED TOP PLUG WITH 1400 psi AT 10:15 AM 12-4 19 90
FLOAT (HELD) (DIDN'T HOLD) PLUG DISPLACED WITH 170.5 bbls Fresh Wtr.

DOWN HOLE CEMENT EQUIPMENT LOCATION: (ALL DEPTHS FTKB)

GUIDE SHOE INSERT FLOAT SCRATCHERS
FLOAT SHOE 2827 BAFFLE
TEX. PAT. SHOE STAGE COLLAR
FLOAT COLLAR 2783 MARKER JT.
CENTRALIZERS 2806, 2743, 2700, 2571, 617, 578

CASING HEAD DISC. REMARKS PIPE DRIFTED ON RACK ☐

REPORTED BY

P. Stenson / R. Bates