

COLLINS & WARE, INC.
JULY 10, 1995

ATTACHMENT TO C-105
PEOC "15" STATE #1
EDDY COUNTY, NEW MEXICO

PERFORATION RECORD FOR RECOMPLETION

Bone Springs 6531' to 6675' - 16 holes

ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. FOR RECOMPLETION

CIBP @ 11,410 w/ 35 sx cement on top
CIBP @ 8,618 w/ 35 sx cement on top
CIBP @ 6,475 w/ 35 sx cement on top
Spot 14 sx plug @ 6440'
Spot 25 sx "C" plug @ 4813' - Tag TOC @ 4741'
Spot 10 sx "C" plug @ 4702' - Tag TOC @ 4714'
Respot 10 sx - Tag TOC @ 4663'
Spot 30 sx plug @ 2882'
Spot 30 sx plug @ 666'
Spot 15 sx plug @ Surface

Squeezed @ 6305' w/ 300 sx - TOC 6155'
Acidized 6531 to 6675 w/ 250 gal 15% NeFe HCL
Fracture Treated 6531 to 6675 w/ 63,000 gal 35H Borate XL gel & 103,000# Ottawa
16/30 sand & 47,500# Resin Coated Sand