

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NMP
OF COPIES REQ'D.
(Other instructions on re-
verse side)

BLM Roswell District
Modified Form No.
NM60-3160-4

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3a. Area Code & Phone No. 505/748-1471		5. LEASE DESIGNATION AND SERIAL NO. NM 65418
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION ✓				6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210				7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 430' FEL, Sec. 14-22S-31E		10. FIELD AND POOL, OR WILDCAT Undes. Livingston Ridge-		8. FARM OR LEASE NAME Delores AIL Federal
		11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA Unit A, Sec. 14-T22S-R31E		9. WELL NO. 1
14. PERMIT NO. 30-015-26547		15. ELEVATION (Show whether OF, RT, GR, ABIF, or OTHER) 3558' GR		12. COUNTY OR PARISH Eddy
				13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☒

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETION ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole 3:35 PM 2-16-91 with Frank's Rathole Service. Set 40' of 20" conductor and cement to surface with redi-mix. Notified BLM, Carlsbad, NM of spud. Resumed drilling 17 1/4" hole 3:00 PM 2-17-91. Ran 20 joints 13-3/8" 54.5# J-55 ST&C casing set 855'. Guide shoe set 855', insert float set 810'. Cemented w/575 sx Class "C" Lite + 2% CaCl2 (yield 1.76, wt 12.8). Tailed in w/200 sx Class "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 11:40 PM 2-18-91. Bumped plug to 600 psi, released pressure, float held OK. Circulated 300 sacks. WOC. Drilled out 7:15 PM 2-19-91. WOC 19 hrs and 35 minutes. Reduced hole to 12-1/4" and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Supervisor

DATE 2-21-91

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS