

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit H, 1980' FNL, 430' FNL, Sec. 14-T22S-R31E

5. Lease Designation and Serial No.

NM 65418

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Dolores AIL Federal #3

9. API Well No.

30-015-26722

10. Field and Pool, or Exploratory Area

Und. Livingston Ridge Delaware

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other Spud, Set Surface

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole 3:00 PM 6-1-91 with rathole. Set 40' of 20" conductor and cemented to surface with redi-mix. Notified BLM, Carlsbad, NM, of spud. Resumed drilling 17 1/2" hole 8:15 PM 6-3-91. Ran 20 joints 13-3/8" 54.5# J-55 casing set 855'. Guide shoe set 855', insert float set 813'. Cemented w/500 sx Pacesetter Lite "C" + 10#/sx Salt + 1/4#/sx Cellsocel (yield 1.76, wt 12.9). Tail in w/250 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 1:57 PM 6-6-91. Bumped plug to 400 psi, released pressure and float held okay. Circulated 150 sacks. WOC. Drilled out 1:15 PM 6-7-91. WOC 23 hrs and 15 minutes. NU and tested to 500 psi for 15 minutes, OK. Reduced hole to 11". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Carla Dauder

Title Production Supervisor

Date 6-11-91

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date

SJS

2 199