RECEMED

Form 3160-5 (June 1990)

Notice of Intent

Subsequent Report

Final Abandonment Notice

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

AUG 0 % 1991

FORM APPROVED Budget Bureau No. 1004-0135

Q. C. D.

Expires: March 31, 1993 5. Lease Designation and Serial No.

Change of Plans

Water Shut-Off

Dispose Water

New Construction

Non-Routine Fracturing

Conversion to Injection

IA, OFFICE	NM 43556

SUNDRY NOTICES AND RE Do not use this form for proposals to drill or to d Use "APPLICATION FOR PERMI"	6. If Indian, Allottee or Tribe Name				
SUBMIT IN TRIE	7. If Unit or CA, Agreement Designation				
1. Type of Well Signature Gas Other		8. Well Name and No. Unocal AHU Federal #2 9. API Well No. 30-015-26786			
105 South 4th St., Artesia, NM 88210	0 (505) 748-1471	10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit A, 660' FNL, 660' FEL, S.ec. 1-T22S-R31E		Und. Lovingston Ridge 11. County or Parish, State Delawar Eddy, NM			
2. CHECK APPROPRIATE BOX(S) TO IN	IDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA			
TYPE OF SUBMISSION	TYPE OF ACTION				

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log (orm.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Other ____

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

Spudded 26" hole 11:40 AM 7-18-91 with rathole. Ran 40' of 20" conductor and cemented to surface with redimix. Notified Nellie Hernandez, BLM, Carlsbad, NM, of spud. Resumed drilling 17½" hole 8:15 PM 7-26-91. Ran 21 jts 13-3/8" 54.5# J-55 casing set at 873'. Guide shoe set 873', insert float set 833'. Cemented w/500 sx Pacesetter Lite "C" + 10#/sx salt + 1/4# sx Celloseal (yield 1.76, wt 12.8). Tail in w/250 sx "C" + 2% CaC12 (yield 1.32, wt 14.8). PD 1:30 AM 7-28-91. Bumped plug to 550 psi, held okay. Circulated 200 sacks cement. WOC. Drilled out 10:30 PM 7-28-91. WOC 21 hrs. NU and tested to 500 psi for 15 minutes. Reduced hole to 11" and resumed drilling.

14. I hereby certify that the foregoing is rue and correct	Title Production Supervisor			Date	7-30-	-91
(Phis/Space-for Federal or State office use)		ACCEPTED FOR REGO				
Approved by	Tide			S 7	- 1	di ingle caracina
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly or representations as to any matter within its jurisdiction.	and willfully to make to any department or agency o	1		A 1551 A 155	itious or fr	raudient statement
•	See Instruction on Reverse Side		KLOBAU		WEAIL	U