RECEIVED

Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

P.O. Box 2088

U-C-4 1991

30-015-26812

OIL CONSERVATION DIVISION WELL API NO.

O. C. D. ARTERIA OFFICE Revised 1-1-89

	DISTRICT II P.O. Drawer DD, Artesia, NM	88210
--	---	-------

CONDITIONS OF APPROVAL, IF ANY: *

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPUCATION FOR PERMIT"	5. Indicate Type of Lease STATE XX FEE 6. State Oil & Gas Lease No. VB-65
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"	6. State Oil & Gas Lease No.
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"	
THE PROPERTY OF THE PROPERTY O	<u> </u>
(FORM C-101) FOR SUCH PROPOSALS 1	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL XX WELL OTHER	RJR State
STATE COST ANT	8. Well No.
3. Address of Operator	9. Pool name or Wildcat
P. O. BOX 10505, MIDLAND, TEXAS 79702	WILDCAT DELAWARE
Unit Letter P: 600 Feet From The East Line and 330 Section 26 Township 24 South Range 27 East NM 10. Elevation (Show whether DF, RKB, RT, GR, etc.)	Feet From The South Line 1PM Eddy County
Check Appropriate Box to Indicate Nature of Notice, Repo	ort, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
ERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OF	_
JLL OR ALTER CASING CASING TEST AND CEME	
THER: OTHER: Perf's & T	[esting XX]

- 9/27/91 Perforated Brushy Canyon/Delaware, 88 holes from 5814-5848', ran packer and acidized w/2000 gallons, swabbed,
- 9/29/91 Frac'd down casing @ 20 BPM @ 1500 PSI w/8000 gal YF135 (35# borate crosslink), 16,800# 20-40 Ottowa sand, 20,400# Sandral LC & 5810 gal. of WF 135 or WF 110 for flush. Swabbed.
- 11/25/91 Set bridge plug at 5,785'. Perforated with 4" casing gum, 1 shot per foot @ 4,571'-4,581', total of 11 holes, dump 4 sxs cement on bridge plug. Loaded hole w/2% KCL water, spot 200 gal 15% NEFE acid, acidize perfs. Opened well after frac and flowing back load.

SIONATURE - Dim	on above in true and complete to the best of my knowledge and belief. TITLE Product:	ion Clerk DATE 12/2/91
(This space for State Use)	ORIGINAL SIGNED BY	TELEPHONE NO.
APPROVED BY	MIKE WILL'AMS SUPERVISOR, DISTRICT IS	BEC 1 3 1991