

+ 15P
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED
FEB 13 1992

O. C. D.

ARTESIA OFFICE

WELL API NO.

30-015-26875

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-2705

7. Lease Name or Unit Agreement Name

Graham AKB State

8. Well No.

1

9. Pool name or Wildcat

Undes. Lost Tank Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter A : 660 Feet From The North Line and 330 Feet From The East Line

Section 2

Township 22S

Range 31E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3546' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 2:20 AM 2-5-92. Set 40' of 20" conductor and cemented to surface. Notified NMOCD, Artesia, NM of spud. Resumed drilling 17-1/2" hole 12:00 NOON 2-6-92. Ran 20 joints 13-3/8" 54.5# J-55 casing set 879'. Guide shoe set 879', insert float 833'. Cemented w/100 sx "H" with 12% Thixad (yield 1.38, wt 15.2), and 600 sx Lite "C" w/2% CaCl2 and 1/2#/sx celloseal (yield 1.76, wt 12.9). Tailed in w/250 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 7:41 PM 2-7-92. Bumped plug to 800 psi, held OK. Circulated 75 sacks cement. WOC. Drilled out at 10:15 PM 2-8-92. WOC 25 hrs adn 34 mins. NU and tested to 500 psi for 15 mins. Reduced hole to 11" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor

DATE 2-11-92

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

FEB 17 1992

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: