Submit 3 Copies to Appropriate District Office	State of New Mexico Energ, Minerals and Natural Resources Department		Form C-103 Revised 1-1-89		
DISTRICT I P.O. Box 1980, Hobbe, NM 88240 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	OIL CONSERVATIO P.O. Box 200 Santa Fe, New Mexico	88 87504 2088 JAN 1 6 1992 O. C. D.	WELL API NO. 30-015-26877 5. Indicate Type of Lesse STATE X FEE 6. State Oil & Gas Lesse No. LH-1523 LH-1523		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name State 2		
OL WEL CAS WEL OTHER 2 Name of Operator Pogo Producing Company Image: Company 3 Address of Operator P.O. Box 10340, Midland, Texas 79702-7340			8. Well No. 3 9. Pool same or Wildcat		
4. Well Location	<u>10</u> Feet From The South Township 22 South Ra	Line and330	Undesiginated - Delaware Foot From The East Line MMPM Eddy County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO:					
		REMEDIAL WORK			
EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB					
OTHER: TD, Run Production Casing X OTHER:					

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 8415', T.D. @ 06:45 hrs. CST December 13, 1991. Schlumberger ran logs, set 5-1/2" 15.50# & 17.0# casing, shoe @ 8415', FC @ 8367', cmt stage tool @ 6186', BJ cemented 1st stage with 630 sx "H" 15.8 ppg, Land plug with 2000#, open DV tool, Circ 5 hrs between stages, circ 100 sx to pit, cmt 2nd stage with 860 sx "C" 35:65:6, 12.5 ppg, tail cmt 200 sx "C" neat 14.8 ppg, did not circulate. Job complete 04:30 hrs. CST, December 15, 1991. Perf 5-1/2" casing @ 700' with 2 holes BJ cmted 5-1/2" casing with 140 sx "C" 35:65:6 with 2% CACl₂, 12.5 ppg followed by 75 sx "C" neat, 14.8 ppg, circ 50 sx, Job complete 15:20 hrs. CST, December 17, 1991, WOC 24 hrs.

I hereby certify that the info	accention above is true and complete to the best of my known	viotge and beli	a. Division Oper. Supt.	DATE Jan. 15, 1992
TYPE OR FRINT NAME	Richard L. Wright			TELEPHONE NO.(915)682-6822
(This space for State Use)	ORIGINAL SIGNED BY HEAL WE LIAMS			FEB 2 8 1992
APPROVED BY		πile -		DATE
CONDITIONS OF APPROVAL	- PANY-			