Corm 3160-5 (November 1983) Formerly 9-331)	DEPARTM	UNITED STATE	INTERIOR	(Other instructions	TC- Ex 5. LEAS	Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DEHIGNATION AND BERIAL NO. NM - 16331		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					6. IF IN	G. IF INDIAN, ALLOTTER OR TEIRE NAME		
I. OIL CAS WELL WELL OTHER				RECEIVED	7. UNIT	7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR Bird Creek Resources, Inc.				FEB - 4 1992		8. FARM OR LEASE NAME BCR Fed.		
3. ADDELESE OF OPERATOR 810 South Cincinnati, Suite 110 Tulsa, OK 74110 O.C.D.						9. WELL NO. 1		
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 						10. FIELD AND POOL, OF WILDCAT Undesignated		
640' FNL, 330' FEL, Unit A Sec. 3 T-23-S R-28-E						11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA 3-235-28E		
14. PERMIT NO.		15. ELEVATIONS (Show 3016.	whether рг, ят, с 5°GR	IR, etc.)	12. COU	NTT OR PARISE dy	18. <i>s</i> tate NM	
16.	Check Ap	propriate Box To I	ndicate Natur	e of Notice, Report, o	r Other Do	ita.		
NOTICE OF INTENTION TO :					UBSBQUENT REPORT OF :			
TEST WATER SHUT-O	FT	CLU OR ALTER CASING		WATER SHUT-OFF		REPAIRING W	"BLL	
FRACTURE TREAT	×	IULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CA	BING	
SHOOT OR ACIDIZE	^	BANDON [®]		SHOOTING OR ACIDIZING		ABANDONMEN	T *	
REPAIR WELL	e	HANGE PLANS	X	(Other)				
i			(NOTE: Keport res Completion or Reco	(Nors: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) and give pertinent dates, including estimated date of starting any measured and true vertical depths for all markers and sonce perti-				

The original APD, as approved on 11-27-91, stated that total depth would be 6400'.

We respectfully request permission to drill the 7 7/8" hole to a total depth of 7750', rather than 6400'. This will allow us to penetrate the second Bone Spring Sand and evaluate for hydrocarbons. The 4 1/2" csg. string will then be set 0 0-7750', and will be cemented in 2 stages w/ cement circulated to surface. The 2 stage tool will be set 0 4500'. No other deviations from the approved APD are anticipated.

hereby certify that the foregoing is true and covre	A1	<u>918-582-3855</u>
15 : hereby certify that the foregoing is true and correct SIGNED Brad D. Bucht	TITLE Brad D. Burks, Agent	DATE 1-20-92
(This space for Federal or State office use)		.)
APPROVED BY CONDITIONS OF APPROVAL, IF ANY :		DATE <u>1/31/92</u>

*See Instructions on Reverse Side