AMENDED DRILLING PROGRAM

BTA OIL PRODUCERS Crystal. 9105 JV-P, Well No. 1 1150' FSL and 1650' FEL Sec. 4, T-24-S, E-26-E Eddy County, New Mexico

In conjunction with Form 3160-3, Application for Permit to Drill, BTA Oil Producers submits the following 10 items for pertinent information in accordance with BLM requirements:

- 1. The geologic surface formation is Quaternary.
- 2. The estimated top of geologic marker is as follows:

Delaware	1,611'	Atoka	10,431'
Bone Spring	5.277	Morrow	10,971'
Strawn Lime	10,221'		- /

. The estimated depth at which anticipated water, cil or gas formations are expected to be encountered:

Delaware	1.611'	Atoka	10,431'
Strawn Line	10,221'	Morrow	10,971'

All shows of fresh water and minerals will be reported and protected. A sample will be taken of any water flows and furnished to the BLM, Division of Minerals. All oil and gas shows will be idequately tested for conmercial possibilities reported and protected.

4. Proposed Casing and Cementing program:

lasing Size	Setting <u>From</u>	Depth	veight	Grade	<u>Joint</u>
13-3/8" 9-5/3" 5-1/2" 5-1/2" 5-1/2"	0 0 1.000' 10.000'	000' 3,300' 1,000' 10,000' 12,200'	54.5= 10.0= 20.0= 17.0= 20.0=	J 33 J 33 N80 N80 N80	STC STC LTC LTC LTC

Depending upon availability at the time that the casing is run. equivalent or adequate weights and grades may be substituted.