			RECEIVED	
orm 3160-5  une 1990)		TED STATES		FORM APPROVED
<b> </b>		NT OF THE INTERIOR	<b>A</b> t 14 -	Budget Bureau No. 1004 0135 Expires: March 31, 1993
	BUREAU OF	LAND MANAGEMENT	JUN - 8. 94	5. Lease Designation and Serial No.
	SUNDRY NOTICES	AND REPORTS ON WELLS	· · · •	NM-12845
Do not use this f	form for proposals to di	ill or to deepen or reentry to a differe	0. 0. 0	6. If Indian, Allottee or Tribe Name
	Use "APPLICATION FO	R PERMIT—" for such proposals	WILL BORN OF HEE	
· · · · · · · · · · · · · · · · · · ·	SUBMIT	IN TRIPLICATE		7. If Unit or CA, Agreement Designation
. Type of Well			1	
KA Well Well	Other	CONFIDE	NTIAL	8. Well Name and No.
. Name of Operator				Federal "1" #6
<u>POGO Produc</u> Address and Telephone	ing Company	é Negyval sztráci, szereszte szereszteretetetetetetetetetetetetetetetetetet	ante arcanacionación	9. API Well No.
				30-015-26910
P.U. Box 10	340, Midland, TX	79702-7340 (915-682-6822)		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey D		escription)		Lost Tank, Delaware
900' FSL, 1	.880' FWL, Sec. 1,	T-22-S, R-31-E		11. County or Parish, State
				Eddy Co., NM
CHECK	APPROPRIATE BOX	s) TO INDICATE NATURE OF NOT		• ,
	SUBMISSION			I, OR OTHER DATA
Notice o			E OF ACTION	
	DI INIENT	Abandonment		Change of Plans
XX Subsequ	ent Report	Recompletion		New Construction
AAS Subsequ	cin Report	Plugging Back		Non-Routine Fracturing
	bandonment Notice	Casing Repair		Water Shut-Off
		Altering Casing XII Other <u>Interm</u> ediate	0 ( 6 9	Conversion to Injection
		ALL Other	e usy	L_I Dispose Water (Note: Report results of multiple completion on Wet
	mpleted Operations (Clearly state all	pertinent details, and give pertinent dates, including estinated depths for all markers and zones participated to this		Completion or Recompletion Report and Log form
		and an indicates and zones permiting to this wor		
Drilled 11" 4280', F.C. 200 sks "C"	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl2 14.8	D. reached 01:15 hrs CST 3-1 n cmt'd csg w/ 1500 sks PSL ' 3 PPg. Plug dn @ 13:00 hrs C Tested BOP's to 2000 Psig.	17-92. Ran 'C" w/ 5% sa CST 3-17-92	
Drilled 11" 4280', F.C. 200 sks "C"	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl2 14.8	D. reached 01:15 hrs CST 3-1 cmt'd csg w/ 1500 sks PSL ' PPg. Plug dn @ 13:00 hrs (	17-92. Ran 'C" w/ 5% sa CST 3-17-92	alt 12.8 PPg. Tailed w . Circ 150 sks excess
Drilled 11" 4280', F.C. 200 sks "C"	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl2 14.8	D. reached 01:15 hrs CST 3-1 cmt'd csg w/ 1500 sks PSL ' PPg. Plug dn @ 13:00 hrs (	17-92. Ran 'C" w/ 5% sa CST 3-17-92	alt 12.8 PPg. Tailed w . Circ 150 sks excess
Drilled 11" 4280', F.C. 200 sks "C" cmt. Total	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl <sub>2</sub> 14.8 WOC 12 3/4 hrs.	D. reached 01:15 hrs CST 3-1 cmt'd csg w/ 1500 sks PSL ' PPg. Plug dn @ 13:00 hrs (	17-92. Ran 'C" w/ 5% sa CST 3-17-92	alt 12.8 PPg. Tailed w . Circ 150 sks excess 
Drilled 11" 4280', F.C. 200 sks "C" cmt. Total	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl2 14.8	D. reached 01:15 hrs CST 3-1 cmt'd csg w/ 1500 sks PSL ' PPg. Plug dn @ 13:00 hrs C Tested BOP's to 2000 Psig.	17-92. Ran 'C" w/ 5% sa CST 3-17-92	Alt 12.8 PPg. Tailed w Circ 150 sks excess OR RECOR 1952 NEW M5XN
Drilled 11" 4280', F.C. 200 sks "C" cmt. Total	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl <sub>2</sub> 14.8 WOC 12 3/4 hrs. oregoing is true mid/correct	D. reached 01:15 hrs CST 3-1 cmt'd csg w/ 1500 sks PSL ' PPg. Plug dn @ 13:00 hrs (	17-92. Ran 'C" w/ 5% sa CST 3-17-92	alt 12.8 PPg. Tailed w Circ 150 sks excess
Drilled 11" 4280', F.C. 200 sks "C" cmt. Total	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl <sub>2</sub> 14.8 WOC 12 3/4 hrs. oregoing is true mid/correct	D. reached 01:15 hrs CST 3-1 cmt'd csg w/ 1500 sks PSL ' 3 PPg. Plug dn @ 13:00 hrs ( Tested BOP's to 2000 Psig. 	17-92. Ran 'C" w/ 5% sa CST 3-17-92	Alt 12.8 PPg. Tailed w Circ 150 sks excess 1952 1952 NEW MEXIC. 4-21-92
Drilled 11" 4280', F.C. 200 sks "C" cmt. Total	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl <sub>2</sub> 14.8 WOC 12 3/4 hrs. oregoing is true field correct for the office use)	Div Oper Supt	17-92. Ran 'C" w/ 5% sa CST 3-17-92	Alt 12.8 PPg. Tailed w Circ 150 sks excess 1952 1952 NEW MEXIC. 4-21-92
Drilled 11" 4280', F.C. 200 sks "C" cmt. Total	hole to 4280', T. @ 4236'. Westerr w/ 2% CACl <sub>2</sub> 14.8 WOC 12 3/4 hrs. oregoing is true field correct for the office use)	D. reached 01:15 hrs CST 3-1 cmt'd csg w/ 1500 sks PSL ' 3 PPg. Plug dn @ 13:00 hrs ( Tested BOP's to 2000 Psig. 	17-92. Ran 'C'' w/ 5% sa CST 3-17-92	alt 12.8 PPg. Tailed w Circ 150 sks excess 1002 1002 NEW M5X4  Date4-21-92