Form 3160-5 (June 1990)

Final Abandonment Notice

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

RECEIVED

Set Prod. Casing [

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 MAR 1 1 1992

5. Lease Designation and Serial No.

NM-29233

O. C. D. SUNDRY NOTICES AND REPORTS ON WELLS PATERIA OFFICE 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well 8. Well Name and No. Federal 12 No. 7 2. Name of Operator Pogo Producing Company 9. API Well No. 3. Address and Telephone No. 30-015-26918 P.O. Box 10340, Midland, Texas 79702-7340 (915)682-6822 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Livingston Ridge, Delaware 11. County or Parish. State 1650' FNL & 1650' FWL, Section 12, T-22-S, R-31-E Eddy County, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off

Completion or Recompletion Report and Log form) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 8535'. T.D. reached 21:30 hrs., CST February 17, 1992. BPB logged well - ran 5-1/2" 15.5# & 17# casing - guide shoe @ 8535' - float collar @ 8496' - stage tool @ 6203'. B.J. Cemented 1st stage with 735 sx "H" with 3% KCL 15.9 ppg - circ. 150 sx excess between stages - cemented 2nd stage with 675 sx "C" lite 12.8 ppg - tailed with 100 sx "C" neat 14.8 ppg - tool closed with 3500 psi (ok) Released rig @ 14:00 hrs., CST February 19, 1992.

$\mathcal{L}_{\mathcal{L}}$				
Signed _	_ TitleDiv	ision Operations Supt.	Date	March 9, 1992
(This space for Federal or State office use)				
Approved by	Title		Date	