

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

1992

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Collins & Ware, Inc.

3. Address and Telephone No.

303 W. Wall, Suite 2200, Midland, Texas 79701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1433' FSL & 1459' FEL of Sec. 26, T-23-S, R-25-E

5. Lease Designation and Serial No.  
NM 51073

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Muley Federal No. 1

9. API Well No.

3001526975

10. Field and Pool, or Exploratory Area

Horseshoe Bend (Strawn)

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other 4.5" Liner Report  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

A six inch hole was drilled to a total depth of 11,540' K.B. A 4.50" 11.60#/ft., S-95, LT&C liner was run. Top of liner at 8640.30' K.B. Bottom of Liner at 11,538.00' K.B. Float collar at 11,476.41' K.B. Float shoe at 11,538.00' K.B. Cemented with 375 sacks Premium cement with 0.8% Halad 413, 4# Microbond "M"/sk., 0.3% HR-5, and 0.6% gas stop (1.12 cu.ft./sk. yield, 16#/gallon). Displaced with 64 barrels 10# mud and 43 barrels fresh water. Plug down at 1:00 PM July 10, 1992. Waited on cement for 12.25 hours. Drilled 503' of hard cement from 8135' - 8638'. Tested 4.5" liner with 2000 psig for 75 minutes, held O.K. Rig released at 5:00 AM July 12, 1992.

14. I hereby certify that the foregoing is true and correct

Signed

Sheryl S. Jones

Title Agent for Collins & Ware, Inc.

Date July 23, 1992

(This space for Federal or State office use)

Approved by

Title

Ad

Date

Conditions of approval, if any:

5 1992

CARLSBAD, NEW