

RECEIVED

SEP - 3 1993

A.C.D.

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 51073

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

NMNM 87873X

8. Well Name and No.

Muley Fed. #1

9. API Well No.

30-015-26975

10. Field and Pool, or Exploratory Area

Dark Canyon Up. Penn

11. County or Parish, State

Eddy NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Collins & Ware, Inc.

3. Address and Telephone No.

303 W. Wall, Ste. 2200, Midland, TX 79701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1433' FSL & 1459' FEL, J, Sec. 26, T23S, R25E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other P & A

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

CIBP(s) set @ the following depths w/ 35' cement plugs on top of each BP: 11,250', 10,900', 10,700', 10,350', 9,925', 9,600', 8,600'.

Delaware perfs. 4867'-4895'; 58 holes; these are now open.

Propose set CIBP @ 4850' w/35' cement plug on top; this P & A procedure will also include setting a 200' cement plug at top of Bone Springs: 4926'.

Will also set plugs @ 2050' (35 sx) and 356' (50 sx); 10 sx @ surf.

14. I hereby certify that the foregoing is true and correct

Signed Max Guerry

Title Regulatory Mgr.

Date 8-23-93

(This space for Federal or State office use)

Approved by Adam Salameh

Title

PETROLEUM ENGINEER

Date 8/31/93

SEE ATTACHED