

EXHIBIT "D"

equipment should be at least 3,000 psi WP or higher unless otherwise specified.

Bell nipple.

Ram type pressure operated blowout preventer

Ram type pressure operated blowout preventer with blind rams.

Flanged spool with one 3-inch and one 2-inch (minimum) outlet.

2-inch (minimum) flanged plug or gate valve.

2-inch by 2-inch by 2-inch (minimum) flanged tee.

3-inch gate valve.

Ram type pressure operated blowout preventer with pipe rams.

Flanged type casing head with one side outlet.

2-inch threaded (or flanged) plug or gate valve.

Flanged on 5000# WP, threaded on 3000# WP or less.

3-inch flanged spacer spool.

3-inch by 2-inch by 2-inch by 2-inch flanged cross.

2-inch flanged plug or gate valve.

2-inch flanged adjustable choke.

2-inch threaded flange.

2-inch XCH nipple.

2-inch forged steel 90° Ell.

Cameron (or equal.) threaded pressure gage.

Threaded flange.

2-inch flanged tee.

2-inch flanged plug or gate valve.

2 1/2-inch pipe, 300' to pit, anchored.

2 1/2-inch SE valve.

2 1/2-inch line to steel pit or separator.

RES:

Items 3, 4 and 8 may be replaced with double ram type preventer with side outlets between the rams.

The two valves next to the stack on the fill and kill line to be closed unless drill string is being pulled.

Kill line is for emergency use only. This connection shall not be used for filling.

Replacement pipe rams and blind rams shall be on location at all times.

Only type U, LSW and QHC ram type preventers with secondary seals are acceptable for 5000 psi WP and higher BOP stacks.

Type E ram-type BOP's with factory modified side outlets may be used on 3000 psi or lower WP BOP stacks.