Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

| Form | C-103 |
|-------|-----------|
| Revis | ed 1-1-89 |

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

OIL CONSERVATION DIVISION P.O. Box 2088

Santa Fe, New Mexico 875 RECEIVED

WELL API NO. 30-015-27018

| Indicate Type of Le | STATE X | | FEE | ļ |
|---------------------|---------|--|-----|---|
|---------------------|---------|--|-----|---|

| • | 2 4 4 6 3 |
|---|--|
| DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 | 6. State Oil & Gas Lease No. V-3589 |
| | Q.C.D. |
| SUNDRY NOTICES AND REPORTS ON WELL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN O DIFFERENT RESERVOIR. USE "APPLICATION FOR PER ON THE PROPOSALS." | OH PLUG BACK TO A 7. Lease Name or Unit Agreement Name |
| (FORM C-101) FOR SUCH PROPOSALS.) | Pauline ALB State |
| I. Type of Well: OIL GAS WELL COTHER | |
| 2. Name of Operator YATES PETROLEUM CORPORATION | 8. Well No. |
| 3. Address of Operator | 9. Pool name or Wildcat |
| 105 South 4th St., Artesia, NM 88210 | Wildcat Delaware |
| 4. Well Location Unit Letter 0: 660 Feet From The South | Line and 1980 Feet From The East Line |
| | nge 31E NMPM Eddy County |
| ////////////////////////////////////// | GR Y/////// |
| 11. Check Appropriate Box to Indicate I | Nature of Notice, Report, or Other Data |
| NOTICE OF INTENTION TO: | SUBSEQUENT REPORT OF: |
| PERFORM REMEDIAL WORK PLUG AND ABANDON | REMEDIAL WORK ALTERING CASING |
| TEMPORARILY ABANDON CHANGE PLANS | COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT |
| PULL OR ALTER CASING | CASING TEST AND CEMENT JOB X |
| OTHER: | OTHER: |
| Describe Proposed or Completed Operations (Clearly state all pertinent details, awork) SEE RULE 1103. | |
| Spudded 26" hole 8:15 PM 12-29-92. Set 40' | of 20" conductor. Redi-mix to surface. |

Notified NMOCD, Artesia, NM, of spud. Resumed drilling 17-1/2 TD 17-1/2' hole 2:00 AM 1-1-93. Ran 11 joints 13-3/8" 54.5# J-55 casing set at 478'. Guide shoe set 478', insert float set 437'. Cemented w/225 sx PSL "C" + 2% CaCl2 (yield 1.76, wt 12.9). Tailed in w/250 sx "C" + 2% CaCl2 + 1/4#/sx Celloseal (yield 1.32, wt 14.8). PD7:41 AM 1-1-93. Bumped plug to 300 psi, float held OK. Circulated 100 sacks. WOC. Drilled out 8:30 AM 1-2-93. WOC 12 hours and 50 minutes. NU and tested to 500 psi for 15 minutes. Reduced hole to 11" and resumed drilling.

| TYPE OR PRINT NAME (This space for State Use) | Juanita Goodlett ORIGINAL SIGNED BY MIKE WILLIAMS | | JAN 1 2 1993 |
|--|--|---------------------|---------------------------|
| | | | TELEPHONE NO. 505//48-14/ |
| SIGNATURE (S) | ustion above is true and complete to the best of my knowle | Production Supervis | |