

+ C15P
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27021
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-120

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.) **RECEIVED**

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> MAY 28 1992	7. Lease Name or Unit Agreement Name Medano VA State
2. Name of Operator YATES PETROLEUM CORPORATION C. & D.	8. Well No. 5
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Los Medanos Delaware
4. Well Location Unit Letter <u>M</u> : <u>660</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>16</u> Township <u>23S</u> Range <u>31E</u> NMPM <u>Eddy</u> County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>3393' GR</u>

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, surface casing & cement job <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole at 10:30 AM 5-9-93 with Frank's Rathole. Set 40' of 20" conductor pipe. Cement to surface. Notified NMOCD in Artesia of spud. Resumed drilling with rotary tools at 7:00 PM 5-13-93.

TD 502'. Ran 12 joints of 13-3/8" 54.5# J-55 (506.11') of casing set at 502'. Texas Pattern notched guide shoe set at 502'. Insert float set at 462'. Cemented with 225 sacks Pacesetter Lite "C" with 2% CaCl₂ (yield 1.76, weight 12.9). Tailed in with 250 sacks "C" and 2% CaCl₂ (yield 1.32, weight 14.8). PD 6:12 AM 5-14-93. Bumped plug to 600 psi. Float did not hold. Circulated 95 sacks cement. WOC. Drilled out at 1:45 AM 5-15-93. WOC 19 hours and 30 minutes. Nippled up and tested to 500# for 15 minutes, OK. Reduced hole to 12-1/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE May 27, 1993
TYPE OR PRINT NAME Rusty-Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ DATE MAY 28 1993

CONDITIONS OF APPROVAL, IF ANY: