

+ c15P
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27021
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-120

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	RECEIVED MAY 28 1992 C. F. D.
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No. 5
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Los Medanos Delaware
4. Well Location Unit Letter M : 660 Feet From The South Line and 660 Feet From The West Line Section 16 Township 23S Range 31E NMPM Eddy County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3393' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate casing & cement job <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3997'. Ran 89 joints of 9-5/8" 36# & 40# J-55 (4000.09') of casing set at 3997'. Float shoe set at 3997'. Float collar set at 3953'. Cemented with 1250 sacks Pacemaker Lite "C", 1/4#/sack celloseal and 10#/sack salt (yield 1.98, weight 12.8). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.32, weight 14.8). PD 9:15 PM 5-19-93. Bumped plug to 1900#, OK. Cement did not circulate. WOC 5 hours. Ran Temperature Survey and found top of cement at 590'. Ran 1". Tagged cement at 560'. Spotted 205 sacks Class "C". PD 6:45 AM 5-20-93. Circulated 10 sacks to surface. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE May 27, 1993

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE MAY 28 1993

CONDITIONS OF APPROVAL, IF ANY: