

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

JUL 19 1993

WELL API NO. 30-015-27022
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-120
7. Lease Name or Unit Agreement Name Medano VA State
8. Well No. 6
9. Pool name or Wildcat Los Medanos Delaware
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3355' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter N : 330 Feet From The South Line and 1980 Feet From The West Line Section 16 Township 23S Range 31E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3355' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, Resume drilling & surface csg. <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole at 11:00 AM 6-16-93. Set 40' of 20" conductor pipe. Cemented to surface.
NOTE: Notified OCD in Artesia of spud. Resumed drilling (17-1/2" hole) at 8:00 PM 6-17-93.

TD 506'. Ran 11 joints of 13-3/8" 54.5# J-55 (509.06') of casing set at 506'. 1-Texas Pattern notched guide shoe set at 506'. Insert float set at 466'. Cemented with 225 sacks PSL "C" 2% CaCl2 (yield 1.76, weight 12.9). Tailed in with 250 sacks "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 6:44 AM 6-18-93. Bumped plug to 1000 psi, float held okay. Circulated 153 sacks. WOC. Drilled out at 1:15 AM 6-19-93. WOC 18 hours and 30 minutes. Nipped up and tested to 500 psi for 15 minutes, OK. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE July 8, 1993
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE JUL 20 1993

CONDITIONS OF APPROVAL, IF ANY: