

Submit 3 Copies To Appropriate
District Office
DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
DISTRICT II
811 South First, Artesia NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 S. Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-27045

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Little Pecos Valley

8. Well No. 1

9. Pool name or Wildcat
Malaga Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Louis Dreyfus Natural Gas Corporation

3. Address of Operator 14000 Quail Springs Parkway, Suite 600
Oklahoma City, OK 73134

4. Well Location

Unit letter D : 550 feet from the North line and 990 feet from the West line

Section 7 Township 24S Range 29E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
2970'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Set CIBP @ 5,475'. Dump bail 35' of cement on top of Plug. Spot 25 sks @ ~~650'~~ 700' And TAG. Circulate 10 sks @ surface.
Cap well, cut anchors off, clean location.

Note: Surface and production casing circulated cement to surface.
Need ADDITIONAL PLUGS AS Follows
255x @ 4075'
255x @ 2820' & TAG
Install Dry Hole MARKER IAW Rule 202.B.(2).
USE Mud Laden fluid BETWEEN All Plugs



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carla Christian TITLE Regulatory Technician DATE 10/2/00

Type or print name Carla Christian

Telephone No. (405) 749-5263

(This space for State use)

APPROVED BY med steelhead TITLE Field Rep. II DATE 10/27/2000

Conditions of approval, if any:

NOTIFY OGD IN TIME TO WITNESS