

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210
RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
Lease Designation and Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE RECEIVED

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Bird Creek Resources, Inc.

3. Address and Telephone No.

1412 S. Boston, Ste. 550, Tulsa, Okla. 74119

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 660' FEL Sec. 3 - T28S - R28E

JUL 28 '94

O. C. D.

918-582-7013

NM-13233

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Unit P

8. Well Name and No.

Hallwood Federal #1

9. API Well No.

30-015-27083

10. Field and Pool, or Exploratory Area

East Loving Delaware

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Estimate Starting Date of Recompletion - 7/30/94

Proposal:

1. Perforate Delaware "B" sand with 1 spf as follows: 6002, 6004, 6006, 6008, 6010, 6012, 6016, 6026, 6027, 6028, 6042, 6044
Perforate Delaware "C" sand with 1 spf as follows: 6102, 6104, 6106, 6108
2. Set Retrieveable bridge plug at 6120' with 2 saks. frac sand
3. Acidize via 2 7/8" tubing with 1250 gals. 7 1/2 % HCL. Frac via casing (5.5") with 29,000 gals. gelled water with 54,000 # 20/40 and 16/30 frac sand at 30 BPM at 1400 psi.
4. Retrieve bridge plug and place well back on rod pump and test for production Commingled.

14. I hereby certify that the foregoing is true and correct

Signed

Wade J. Oleya

Title Production Superintendent

Date 6/29/94

(This space for Federal or State office use)

Orig. Signed by Shahnon J. Shury

Approved by

Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date 7/26/94