

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir

Use "APPLICATION FOR PERMIT --" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well: ☐ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator: TEXACO EXPLORATION & PRODUCTION INC.

3. Address and Telephone No.: P.O. Box 2100, Denver Colorado 80201 (303)621-4851

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter E 1650 Feet From The NORTH Line and 990 Feet From The

WEST Line Section 24 Township 22-S Range 31-E

5. Lease Designation and Serial No.: NM-25876

6. If Indian, Alottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and Number: GETTY '24 FEDERAL

6

9. API Well No.: 30-015-27084

10. Field and Pool, Exploratory Area: LIVINGSTON RIDGE DELAWARE

11. County or Parish, State: EDDY NEW MEXICO

12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ OTHER: COMPLETION
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1. RU SCHLUMBERGER. RUN GR/CCL FROM PBD @ 8500'-6600'. CORRELATE TO CNL. PERF'D FROM 8264'-8291', 8266'-8302' W/ 2 JSPF. 50 HOLES. 06-21-96.
2. RU DOWELL. SPOT 200 GALS 7.5% HCL TO 8325'. 06-23-96.
3. SET LUFKIN 640D PUMPING UNIT. FRAC'D W/ 9000 GALS 30# BORATE AND 28.400# 16/30 RESIN SAND. 06-25-96.
4. TIH W/ 1 JT BULL PLUGGED 2 7/8" 6.5# WC-50 TBG. SEPARATOR. SN. JTS. LANDED TBG. SET @ 8266'. SN SET @ 8222'. 06-28-96.
5. TIH W/SD SCREEN. 2 1/2" X 1 1/2" X 24' PM. RODS. RU PM JACK AND PUT ON PM TEST @ 7:00 P.M. 06-28-96.
6. PUMPED 43 BO. 39 BW. 67 MCF IN 24 HOURS. 07-05-96.
7. PULL PM AND RODS. TBG. RU SCHLUMBERGER AND SET RBP @ 8250'. TEST TO 3000 PSI. DUMP BAIL 10' SAND ON PLUG. PERF'D 8108'-17', 8129'-42', 8148'-56', 8160'-63'. TH W/ RBP OVERSHOT. SN. TBG. TIH W/ TBG TO 8058'. RU DOWELL. AND ACIDIZED W/1700 GALS 7.5% NEFE. FRAC'D W/22,000 GALS 30# BORATE AND 56.840# 16/30 RESIN SAND. 07-06-96.
8. RUN 2 1/2" X 1 3/4" X 22' PUMP. STARTED RUNNING RODS. 07-08-96.
9. PU PRIDE WELL SERV. PULL PM AND RODS. 07-20-96.
10. RUN TBG. SEPARATOR. SUB. SN @ 8329'. NU HEAD. RUN SD SCREEN. 2 1/2" X 1 1/3" X 24' PM. RODS. 07-21-96.
11. SCHLUMBERGER PERF'D W/2JSPF 7704'-7708', 7713'-7715', 7717'-7722', 7725'-7728'. 28 HOLES. TIH W/ PKR. SN. 2 7/8" TBG. 08-13-96.
12. DOWELL ACIDIZED W/700 GALS 7.5% NEFE ACID. FRAC'D W/10,900 GALS 30# BORATE AND 28,000# 16/30 CURABLE SD. 08-14-96.
13. RUN 2 1/2" X 1 3/4" X 24' PUMP. RODS. 08-17-96.
14. PUMPED 243 BO. 189 BW. 121 MCF IN 24 HOURS. 08-26-96.

14. I hereby certify that the foregoing is true and correct.

SIGNATURE: C. P. Basham / SRH TITLE: Eng. Assistant

DATE: 9-4-96

TYPE OR PRINT NAME: Sheilla D. Reed-High

(This space for Federal or State office use.)

APPROVED

CONDITIONS OF APPROVAL, IF ANY: TITLE: DATE:

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.