Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICTI

OIL CONSERVATION DIVISION

P.O. Box 1980, Hoobs, NM 88240	P.O. Box 20	88	WELL API NO.
DISTRICT II	Santa Fe, New Mexico		30-015-27092
P.O. Drawer DD, Artesia, NM 88210		APR 1 0 1994	5. Indicate Type of Lease STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410		\mathbf{y}_{i}	6. State Oil & Gas Lease No. VB - 0142
SUNDRY NOTICES	AND REPORTS ON WEL	LS	
(DO NOT USE THIS FORM FOR PROPOSA	LS TO DRILL OR TO DEEPEN	OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
(FORM C-101) F	USE APPLICATION FOR PE		
1. Type of Well: On. GAS WELL X WELL	OTHER		H. Buck State
2. Name of Operator			8. Well No.
Pogo Producing Company 3. Address of Operator			9. Pool name or Wildcat
P. O. Box 10340, Midla	nd. TX 79702-7340		
4. Well Location	114, 17, 7, 702 7010		Undes Bone Springs
Unit Letter J: 1982 Fe	ex From The South	Line and1961	Feet From The East Lin
Section 16 To	ownship 245 Ra	nge 29E N	IMPM Eddy County
	10. Elevation (Show whether I		
11. Check Appro	opriate Box to Indicate N	Nature of Notice Re	port, or Other Data
NOTICE OF INTENT	-	•	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	LUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	HANGE PLANS	COMMENCE DRILLING	OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING		CASING TEST AND CEN	MENT JOB.
OTHER: TD & Production Casi	ing 🔲	OTHER:	·
12. Describe Proposed or Completed Operations (CL work) SEE RULE 1103.	early state all pertinent details, and	i give pertinent dates, includi	ng estimated date of starting any proposed
IRU Nabors Rig #301. Re-enterill cement plugs down to 675 2330 hrs CST 1/15/94. Ran 1 loat collar @ 7800'. Stage tlass "H" + 2.4 pps KCl + 5 pp and plug. Drop bomb and open nd stage w/ 882 sx Class "H" isplace cement and land plug. etween stages. Cement 3rd st lass "C" @ 14.8 ppg. Plug dout-off. Weld on wellhead and	75 jts 5-1/2", 17#, 75 jts 5-1/2", 17#, 500ls @ 6179' and 39 8 Microbond + .6% H DV tool @ 6179'. + 2.4 pps KCl + 5 p Drop bomb and ope age w/ 955 sx Halli wn @ 2030 hrs CST 1	hole from 6750' J-55, LT&C casi 72'. Howco ceme alad 322 @ 15.6; Circulate 5 hrs ps Microbond + .4 n DV tool @ 3978	ng. Guide shoe @ 7850'. nted Ist stage w/ 475 sx ppg. Displace cement and between stages. Cement 4% Halad 322 @ 15.6 ppg. '. Circulate 5 hrs
			· · · · · · · · · · · · · · · · · · ·
I hereby certify that the juffernation above is true and comp	olete to the best of my knowledge and be	elief.	1801 7 1994
SIGNATURE		المحمودية المستحدث المستحدث المستحدث المستحدد المستحدد المستحد المستحدد الم	<u> </u>
TYPE OR PRINT NAME			TELEPHONE NO.
(This space for State Use)			

SUPERVISOR, DISTRICT II

APPROVED BY -

APR 1 5 1994