Form 3160-5 (June 1990)

1. Type of Well

X Well

2. Name of Operator

Other

Devon Energy Corporation (Nevada)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED
Budget Bureau No. 1004-013:
Expires: March 31, 1993

				_	_
5.	Lease	Designation	and	Serial	No

NM 0405444-A 6. If Indian, Allonee or Tribe Name

N/A

9. API Well No.

8. Well Name and No.

SUNDRY NOTICES AND REPORTS ON WELLS	
this form for proposals to drill or to deepen or reentry to a different reservo	ir.

Do not use Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

N/A 7. If Unit or CA, Agreement Designation

Todd "26" Federal #11

3. Address and Telephone No.		30-015-27103			
20 N. Broadway Suite 1500 O	klahoma City, OK 73102 (405)235-3611	10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey De	Undesignated Delaware				
Section 26-T23S-R31E	11. County or Parish, State				
890' FEL & 990' FNL					
		Eddy County, NM			
12 CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA			
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	Abandonmeni	Change of Plans			
X Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing			
Final Abandonment Notice	Casing Repair Altering Casing Other set intermediate casin	Water Shut-Off Conversion to Injection Or Dispose Water			
13 Describe Proposed or Completed Operations (Clearly state all		(Note: Report results of multiple completion on Well- Completion or Recompletion Report and Log form 1			
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled,					

On 10/11/92, we set 4450' of 8 5/8" 32# ST&C intermediate casing in an 11" open hole.

pumped the following cement slurries:

Lead Slurry: 2100 sks 35:65 (Poz: Class C) + 6% gel + 15 lb/sk salt + 0.25 lb/s cellophane flakes

200 sks Class C + 2% CaCl2 + 0.25 lb/sk cellophane flakes Tail Slurry:

Cement was circulated to surface (circulated 175 sks to the pit). The BLM was contacted prior to the job, but no witness was present.

2 8 1990

,		
14. I hereby certify that the foregoing is frue and correct Signed	Charles W. Horsman Tide _ District Engineer	Date 10/12/92
(This space for Federal or State office use)		
Approved by Conditions of approval, if any.	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction