

## AUXILIARY EQUIPMENT

DRAWWORKS	BDW 650M 650 HP, with Parmac Hydromatic brake
ENGINES	Two Caterpillar D-353 diesels rated at 425 HP each
ROTARY	Ideco 23", 300 ton capacity
MAST/SUB	Ideal 132',550,000 lb rated static hook load with 10 line Wagner 15' high substructure
TRAVELLING EQUIPMENT	Gardner-Denver,300 ton,5 sheave w/ BJ 250 ton hook. Brewster Model 7 SX 300 ton swivel.
PUMPS	Continental-EMSCO DC-700 and DB-550, 5 1/2 X 16" Duplex, Compound driven.
PIT SYSTEM	1-Shale Pit 6X7X35',1-Settling Pit 6X7X38', 1-Suction Pit 6X7X34' w/ 5 mud agitators. Two centrifugal mud mixing pumps and a Double Screen Shale Shaker.
LIGHT PLANT	Two CAT 3306 diesel electric sets 180 KW prime power.
BOP EQUIP	13 5/8" 5000 psi WP double ram and 13 5/8" 5000 psi WP Shaffer Annular Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon closing unit.

Exhibit D  
Santa Fe Energy Operating Partners,L.P.  
Pure Gold C-17 No.4  
Section 17, T-23S,R-31E  
Eddy County, New Mexico

DDR:PGC174