

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator YATES PETROLEUM CORP.		Lease PAULINE "ALB" STATE		Well # 7	
Location of Well	Unit M	Section 32	Township 23	Range 31	County EDDY
Drilling Contractor	Undesignated		Type of Equipment Rotary		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	* 13 3/8	54.5#		500	700 Circ.
11	* 8 5/8	32#		4200	2800 Circ
7 7/8	* 5 1/2	17# & 15.5#		8200 TD	800

Casing Data:

Surface _____ joints of 8 5/8" inch 32 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. _____ date Dec. 18-92

Cementing Program

Size of hole 11" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 3981' Set 3981' Feet of 8 5/8" Inch 32 # Grade J-55

New-used csg. @ 3981' with 200 (225) sacks neat cement around shoe
+ 1575 sax Passetter Lite - C additives 10# salt, 1/4# cello-seal

Plug down @ 2:15 (AM) (PM) Date Dec. 23-92

Cement circulated Yes No. of Sacks 225 sx

Cemented by Western Company Witnessed by Mike Stubblefield

Temp. Survey ran @ (AM) (PM) Date _____ top cement @ _____

Casing test @ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____