

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

dst
89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

JAN 05 1993

WELL API NO.
30-015-27155

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-3589

7. Lease Name or Unit Agreement Name

Pauline ALB State

8. Well No.
7

9. Pool name or Wildcat
Wildcat Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter M : 660 Feet From The South Line and 660 Feet From The West Line
Section 32 Township 23S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3383' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 2:00 PM 12-14-92. Set 40' of 20" conductor pipe and cement to surface. Notified NMOC, Artesia, NM of spud. Resumed drilling 17 1/2" hole 4:00 PM 12-17-92. TD 17 1/2" hole 2:45 AM 12-18-92. Ran 12 joints 13-3/8" 54.5# J-55 ST&C casing set 506'. Guide shoe set 506', insert float set 463'. Cemented w/225 sx PSL "C" w/1/4#/sx Celloseal, 2% CaCl2 (yield 1.32, wt 14.8). PD 8:00 AM 12-18-93. Bumped plug to 300 psi, float held OK. Circulated 150 sacks. WOC. Drilled out 12:30 PM 12-19-92. WOC 28 hrs and 30 minutes. NU and tested to 1000 psi for 30 minutes. Reduced hole to 11" and resumed drilling. Ran 89 joints 8-5/8" 32# J-55 casing set 3988', float shoe set 3988', float collar set 3943'. Cemented w/1575 sx PS "C" w/10#/sx Salt, 1/4#/sx Celloseal (yield 2.0, wt 12.6). Tailed in w/200 sx Class "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 2:15 AM 12-23-92. Bumped plug to 1800 psi, float held OK. Circulated 270 sacks. WOC. Drilled out 3:00 AM 12-24-92. WOC 24 hours and 45 minutes. NU and tested to 1000 psi for 15 minutes, OK. Reduced hole to 7-7/8", resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 1-4-93

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE SUPERVISOR DATE JAN 12 1993

CONDITIONS OF APPROVAL, IF ANY: