

+clsf  
up

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240  
DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210  
DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

RECEIVED  
MAR 04 1993

WELL API NO. 30-015-27156
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-3589
7. Lease Name or Unit Agreement Name Pauline ALB State
8. Well No. 8
9. Pool name or Wildcat West Sand Dunes Delaware

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
Name of Operator YATES PETROLEUM CORPORATION ✓
Address of Operator 105 South 4th St., Artesia, NM 88210
Well Location Unit Letter <u>L</u> : <u>1980</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>32</u> Township <u>23S</u> Range <u>31E</u> NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3365' GR
--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 11:00 AM 2-6-93. Set 40' of 20" conductor and cemented to surface. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 17-1/2" hole NOON 3-1-93. Ran 11 joints 54.5# J-55 casing set at 501'. Guide shoe set at 501', insert float set at 454'. Cemented w/250 sx PSL "C" + 2% CaCl2 (yield 1.76, wt 12.9). Tailed in w/250 sx "C" + 2% CaCl2 + 1/4#/sx Celloseal (yield 1.32, wt 14.8). PD 1:13 AM 3-2-93. Bumped plug to 400 psi, held OK. Circulated 125 sacks cement. WOC.

Drilled out 2:00 AM 3-3-93. WOC 24 hours and 45 minutes. Reduced hole to 11" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-3-93

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAR 16 1993

CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_