Form 3160-5 (June 1990)

LEVENED UNITED STATES DEPARTMENT OF THE INTERIOR 1 2 BUREAU OF LAND MANAGEMENT

1992

FORM APPROVED Budget Bureau No. 1004-0135

Expires:		March 31, 1993			
1		Decigos	ion and	Serial No.	

NM-77046 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE Type of Well 8. Well Name and No. XX Oil Well North Pure Gold "9" Fed #1 Name of Operator 9. API Well No. Santa Fe Energy Operating Partners, L.P 30-015-27178 3 Address and Telephone No. 10. Field and Pool, or Exploratory Area 550 W. Texas, Suite 1330, Midland, TX 79701 (915) 687-3551 Sand Dunes West (Delaware) 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 1980' FWL and 330' FSL, Sec. 9, T-23S, R-31E Eddy Co., New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent New Construction Recompletion Non-Routine Fracturing Plugging Back XX Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Dispose Water string & RR Other Ran csg (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* 11-7-92: Reach TD of 8125'. Logging. 11-8-92: RU casing crew and begin running 5-1/2" csg. WO float collar. 11-9-92: Finished running total of 194 jts 5-1/2" 15.5# & 17# J-55 & K-55 casing and set at 8125. FC at 8048. Marker collar @ 7502' and DV tool @

6007'. Circ 5-1/2" casing. Cemented 1st stage w/ 700 sx "H" + .8% FL-62 + 5 sx KCl. Float held. Open DV tool and circ. Cemented 2nd stage w/ 500 sx "C" Lite (35:65:5). Tail w/ 400 sx "C" Neat. ND BOP. Set slips w/ 110,000# on slips. Cut off 5-1/2" csg. NU tbg head and test to 3000 psi. Released rig at 5:00 p.m. CST. WOCU.

Signed C C C C C C C C C C C C C C C C C C C	Title Sr. Production Clerk	Date Nov. 11, 1992
(This space for Federal or State office use)  Approved by Conditions of approval, if any:	Title	Date