

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, Texas 79702-7340 (915) 682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL and 2310' FEL, Section 35, T-23-S, R-31-E

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-19199

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cal-Mon No. 9

9. API Well No.

30-015-27206

10. Field and Pool, or Exploratory Area

Ingle Wells, Delaware

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud and Set Surface Casing  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud and Set Surface Casing

MIRU Exeter Rig #66. Spud @ 1600 hours CST 12/06/92. Drilled 17-1/2" hole to 815'. TD reached 1730 hours CST 12/07/92. Ran 19 jts 13-3/8", 54.50#, J-55, ST&C casing. TPGS @ 815'. IFV @ 771'. Halliburton cemented casing with 750 sx Halliburton Lite + 2% CACL @ 12.7 PPG, followed by 200 sx "C" + 2% CACL @ 14.8 PPG. Plug down with 600 PSI 0015 hours CST 12/07/92. Circulated 150 sx excess cement. WOC 31 hours. NU BOP's and test to 1,000 PSI.

14. I hereby certify that the foregoing is true and correct

Signed

Title Division Operations Manager

Date

1/12/93

(This space is for State or Federal use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations, or to use any means within its jurisdiction to obtain such information.

CARLOS R. NEW MEXICO

\*See Instruction on Reverse Side