

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

FEB 23 1993

O. C. D.

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P.O. Box 10340, Midland, Texas 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 1650' FWL, Section 28, T-23-S, R-31-E

5. Lease Designation and Serial No.

NM-40659

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pure Gold "D" Fed. No. 8

9. API Well No.

30-015-27219

10. Field and Pool, or Exploratory Area

Sand Dunes West, Delaware

11. County or Parish, State

Eddy County, New Mexico

CONFIDENTIAL

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud & Set Surface Csg.  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU Exeter Rig #66. Spud @ 16:00 hrs. CST 01/18/93. Drilled 17-1/2" hole to 570'. TD reached 07:30 hrs. CST 01/19/93. Ran 14 jts. 13-3/8" 54.5#, J-55, ST&C casing. TPGS @ 570'. IFV @ 524'. Howco cemented casing with 525 sx Halliburton Lite + 2% CACL<sub>2</sub> @ 12.7 ppg. Plug down with 550 psi @ 13:30 hrs. CST 01/19/93. Recovered 200 sx excess cement. WOC 24 hrs. NU BOP's and test to 1500 psi.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Division Operations Manager

Date Feb. 22, 1993

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Conditions of approval, if any: \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

CLSF