Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT		Expires: March 31, 1993
		5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS		NM-19199
		6. If Indian, Allottee or Tribe Name
Do not use this form for proposals to d	rill or to deepen or reentry to a different reservoir.	
Use "APPLICATION FO	OR PERMIT—" for such proposals	
		7. If Unit or CA, Agreement Designation
SUBMIT IN TRIPLICATE		Designation
1. Type of Well		-
Oil Gas Other	CONFIDENTIAL	8. Well Name and No.
2. Name of Operator	CONFIDENCE	
Pogo Producing Company	PENTIAL	Calmon 11
3. Address and Telephone No.	ייאנ	<u> </u>
·		30 015 27223
P. O. Box 10340, Midland, TX 79702 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
		Ingle Wells Delaware
1650' FSL & 660' FWL, Sec. 35, T23S, R31E AUG - 9 199 3		11. County or Parish, State
**	800 0 1330	
	C. (, D.	Eddy County, NM
12. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	П., .	Па
Modee of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion	New Construction
	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	LX Other TD & Prod Casing	Dispose Water
:		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state al	pertinent details, and give pertinent dates, including estimated date of starting	any proposed work. If well is directionally drilled
give subsurface locations and measured and true vertice	al depths for all markers and zones pertinent to this work.)*	,
Drilled 7 7/8" hole 4300)' to 8390'. TD reached 1230 hrs CDT 7	//21/93
logged wellwith Western	Atlas. Ran 196 jts-5 1/2", 15.5# & 17	/ LI/ JJ. !# 1 EE 0
1-80 IT&C casing Guid	le shoe @ 8390'. Float collar @ 8342'.	#, 0~55 &
tools @ 5020! 0 4001!	House emented let et a collar 9 8342.	Stage
tools @ 5829' & 4081'. Howco cemented 1st stage with 175 sx Halliburton		
Lite @ 12.4 PPG TOITOWED	by 650 sx Premium Plus @ 13.6 PPG. [rop
bomb & open stage tool @ 5829'. Circulate 5 hrs between stages.		
Recovered 60 sx excess cement. Cement 2nd stage with 525 sx Halliburton		
Lite @ 12.4 PPG followed by 100 sx Premium Plus @ 14.8 PPG. Land		
plug & close DV tool @ 5829'. Drop bomb & open DV tool @ 4081'.		
Circulate 5 hrs between stages. Recovered 100 sx excess cement.		
Cement 3rd stage with 450 sx Halliburton Lite @ 12.4 PPG followed		
-		···

by 50 sx Premium Plus @ 14.8 PPG. Plug down & tool closed @ 1800 hrs CDT 7/22/93. Recovered 70 sx excess cement. Set slips & make cut off.

ND BOP's and well on casing head. Test to 2500 psi.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.