		C
- IN ED	NM OIL COMS. COMMICS Drawar DD	ICA
DEPARTMEN	NT OF THE INTERIOR	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
3 Da . BUREAU OF	LAND MANAGEMENT	5. Lease Designation and Serial No. NM-19199
SUNDRY NOTICES	AND REPORTS ON WELLS	6. If Indian, Allottee or Tribe Name
	rill or to deepen or reentry to proposals	
	TIN TRIPLICATE	7. If Unit or CA, Agreement Designation
Type of Weil Oil Gas X Weil Other Name of Operator Other		8. Well Name and No.
Pogo Producing Company	CONFIDENTIAL	Cal-Mon No. 10
Address and Telephone No. P. O. Box 10340, Midland, Te		30-015-27269 10. Field and Pool, or Exploratory Area
. Location of Well (Footage, Sec., T., R., M., or Survey E		Ingle Wells Delaware
330' FNL & 660' FEL Section 3	35, T-23-S, R-31-E, N.M.P.M.	Eddy County, New Mexico
CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	AbanJonment Recompletion	Change of Plans
X Subsequent Report	Plugging Back	Nun-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Euglorm 3
Describe Proposed or Completed Operations (Clearly state a give subsurface locations and measured and true verti	Il pertinent details, and give pertinent dates, including estimated date of starting ical depths for all markers and zones pertinent to this work.)*	
Describe Proposed or Completed Operations (Clearly state a give subsurface locations and measured and true verti INTERMEDIATE CASING	Il pertinent details, and give pertinent dates, including estimated date of starting cal depths (or all markers and zones pertinent to this work.)*	
give subsurface locations and measured and true verti INTERMEDIATE CASING Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900	ical depths for all markers and zones pertinent to this work.)* 95'. TD reached 0900 hours CST 3/08/93 9g. Guide Shoe @ 4,305'. Float Colla 9 Halliburton Lite @ 12.7 PPG followed b 9 hours 3/08/93. Float held. Recovered	any proposed work. If well is directionally drilled. 3. Ran 102 jts - 8-5/8", r @ 4,260'. Howco by 200 sx Premium Plus
give subsurface locations and measured and true verti <u>INTERMEDIATE CASING</u> Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx	ical depths for all markers and zones pertinent to this work.)* 95'. TD reached 0900 hours CST 3/08/93 9g. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 9 hours 3/08/93. Float held. Recovere 9P's to 1500 PSI.	3. Ran 102 jts - 8-5/8", r @ 4,260'. Howco by 200 sx Premium Plus ed 200 sx excess cement.
give subsurface locations and measured and true vertice INTERMEDIATE CASING Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900	ical depths for all markers and zones pertinent to this work.)* 95'. TD reached 0900 hours CST 3/08/93 9g. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 9 hours 3/08/93. Float held. Recovere 9P's to 1500 PSI.	any proposed work. If well is directionally drilled. 3. Ran 102 jts - 8-5/8", r @ 4,260'. Howco by 200 sx Premium Plus
give subsurface locations and measured and true vertice INTERMEDIATE CASING Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900	ical depths for all markers and zones pertinent to this work.)* 95'. TD reached 0900 hours CST 3/08/93 9g. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 9 hours 3/08/93. Float held. Recovere 9P's to 1500 PSI.	3. Ran 102 jts - 8-5/8", r @ 4,260'. Howco by 200 sx Premium Plus ed 200 sx excess cement.
give subsurface locations and measured and true vertice INTERMEDIATE CASING Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900	ical depths for all markers and zones pertinent to this work.)* 15'. TD reached 0900 hours CST 3/08/93 19. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 10. hours 3/08/93. Float held. Recover 10. P's to 1500 PSI. ACCEPTI	B. Ran 102 jts - 8-5/8", c @ 4,260'. Howco by 200 sx Premium Plus ed 200 sx excess cement. ED FOR RECORD
give subsurface locations and measured and true verti INTERMEDIATE CASING Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900	ical depths for all markers and zones pertinent to this work.)* 15'. TD reached 0900 hours CST 3/08/93 19. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 10. hours 3/08/93. Float held. Recover 10. P's to 1500 PSI. ACCEPTI	3. Ran 102 jts - 8-5/8", r @ 4,260'. Howco by 200 sx Premium Plus ed 200 sx excess cement.
give subsurface locations and measured and true verti <u>INTERMEDIATE CASING</u> Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900 NU BOP's. Test casing and BC	ical depths for all markers and zones pertinent to this work.)* 15'. TD reached 0900 hours CST 3/08/93 19. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 10. hours 3/08/93. Float held. Recover 10. P's to 1500 PSI. ACCEPTI	Any proposed work. If well is directionally drilled. B. Ran 102 jts - 8-5/8", r @ 4,260'. Howco by 200 sx Premium Plus ed 200 sx excess cement. ED FOR RECORD
give subsurface locations and measured and true verti <u>INTERMEDIATE CASING</u> Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900 NU BOP's. Test casing and BC NU BOP's. Test casing and BC	Ead depths for all markers and zones pertinent to this work.)* 15'. TD reached 0900 hours CST 3/08/93 19. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 10. hours 3/08/93. Float held. Recovered 10. Pr's to 1500 PSI. ACCEPTI 10. AP CARLSBA Barrett L. Smith	Annih 15 - 1002
give subsurface locations and measured and true vertice INTERMEDIATE CASING Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900 NU BOP's. Test casing and BO NU BOP's. Test casing and BO 4. I hereby certify that the foregoing is true and correct Signed	Ead depths for all markers and zones pertinent to this work.)* 15'. TD reached 0900 hours CST 3/08/93 19. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 10. hours 3/08/93. Float held. Recovered 10. Pr's to 1500 PSI. ACCEPTI 10. AP CARLSBA Barrett L. Smith	Annih 15 - 1002
give subsurface locations and measured and true vertil INTERMEDIATE CASING Drilled 11" hole 818' to 4,30 24# and 32#, J-55, ST&C casin cemented casing with 1650 sx @ 14.8 PPG. Plug down @ 1900 NU BOP's. Test casing and BO NU BOP's. Test casing and BO 4. I hereby certify that the foregoing is true and correct signed	DS'. TD reached 0900 hours CST 3/08/93 19. Guide Shoe @ 4,305'. Float Collan Halliburton Lite @ 12.7 PPG followed H 0 hours 3/08/93. Float held. Recovered 0 P's to 1500 PSI. ACCEPTI 10 CARLSBA Barrett L. Smith Tide Senior Operations Engineer	A set any proposed work. If well is directionally drilled. B. Ran 102 jts - 8-5/8", r @ 4,260'. Howco by 200 sx Premium Plus ed 200 sx excess cement. ED FOR RECORD D FOR RECORD D NEW MEXICO Date