

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, Texas 79702-7340

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 660' FEL, Section 35, T23S, R31E

5. Lease Designation and Serial No.

NM-19199

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cal Mon No. 10

9. API Well No.

30-015-27269

10. Field and Pool, or Exploratory Area

Ingle Wells, Delaware

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Perf additions & stimulation
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-14-93 Set RBP @ 8140' (existing perfs 8174' to 8224'). Perf'd 5-1/2" csg thru 8067' to 8112' (1) spf 120° phase w/ 4" csg gun (total of 45 .51" holes)
7-16-93 Well on vacuum. Moved RBP to 7315'. Tested csg & RBP to 3000 psig. Perf'd 5-1/2" csg 7022' to 7041' 2 spf 120° phase w/ 4" csg gun (total of 38 .51" holes)

7-17-93 Acidize perfs 7022 to 7041 w/ 1000 gals 7-1/2% HCL w/ Pentol 100. Broke down w/ 2700 psig - AIR 9.2 BPM. Avg press 4200 psig down 2-7/8" tbg. Zone balled out w/ 5200 psig. Surge balls over flush. ISIP 510 psig 15 min 410 psig.

9-3-93 Frac'd perfs 7022-7041 w/ 37,000 gals X-L fluid pad propped w/ 42,000 lbs 16/30 ottawa sand. Put well on pump. *Adze*

14. I hereby certify that the foregoing is true and correct

Signed *Richard L. Drift*

Title Division Operations Manager

Date 9/16/93

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____