

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-27320
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-120
7. Lease Name or Unit Agreement Name	Medano VA State
8. Well No.	12
9. Pool name or Wildcat	Los Medanos Delaware
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3356' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
YATES PETROLEUM CORPORATION
3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter G : 1650 Feet From The North Line and 2310 Feet From The East Line
Section 16 Township 23S Range 31E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, resume drilling, surface casing and cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 9:15 AM 7-13-96. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Ray Smith w/OCD-Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 9:30 PM 7-14-96.

TD 497'. Reached TD at 10:45 AM 7-15-96. Ran 11 joints of 11-3/4" 42# 8rd H-40 ST&C (501.28') of casing set at 497'. 1-Texas Pattern notched guide shoe set at 497'. Insert float set at 455'. Cemented with 250 sacks Premium Plus "C", 1/4#/sack flocele and 2% CaCl2 (yield 1.33, weight 14.8). Tailed in with 200 sacks Premium Plus "C" and 2% CaCl2 (yield 1.33, weight 14.8). PD 5:15 PM 7-15-96. Bumped plug to 700 psi, OK. Circulated 130 sacks to pit. WOC. Nippled up and tested to 500#. Drilled out at 7:15 PM 7-16-96. WOC 26 hours. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE July 18, 1996
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

JUL 29 1996

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: