

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

+ clsf
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-27325

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VB-120

7. Lease Name or Unit Agreement Name

Medano VA State

8. Well No.
17

9. Pool name or Wildcat
Los Medanos Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter D : 500 Feet From The North Line and 330 Feet From The West Line

Section 16 Township 23S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3342' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 4:20 PM 4-26-93. Set 40' of 20" conductor pipe. Cemented to surface. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 17-1/2" hole 5:30 PM 4-27-93. TD 17-1/2" hole 2:15 AM 4-28-93. Ran 11 joints 13-3/8" 54.5# J-55 casing set 505'. Guide shoe set 505', insert float set 459'. Cemented with 225 sx PSL "C" w/2% CaCl2 (yield 1.76, wt 12.9). Tailed in with 250 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 8:15 AM 4-28-93. Bumped plug to 650 psi, float held OK. Circulated 127 sacks. WOC. Drilled out 4:45 AM 4-29-93. WOC 20 hrs and 30 minutes. NU and tested to 500 psi for 15 minutes, OK. Reduced hole to 12-1/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-29-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

MAY 6 1993

CONDITIONS OF APPROVAL, IF ANY: