

Form 3160-5
(June 1990)

NM OIL CONS. STATISTICAL
Drawer 30
Artesia, NM 88210

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS JUL 18 '94

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals O. C. D.

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P.O. Box 10340, Midland, Texas 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 2310' FEL, Section 28, T-23-S, R-31-E

5. Lease Designation and Serial No.

NM-40659

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pure Gold "D" 12

9. API Well No.

30-015-27347

10. Field and Pool, or Exploratory Area

Sand Dunes, Delaware

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate Casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log (Form 1))

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled 11" hole 570' to 4108'. TD reached 03:15 hrs., CDT 4/22/93.
Ran 97 jts. 8-5/8", 24# & 32#, J-55, ST&C casing. Guide shoe @ 4108'.
Float collar @ 4062'. Howco cemented casing with 1400 sx Halliburton
Lite @ 12.7 ppg followed by 200 sx Premium Plus @ 14.8 ppg. Plug down
@ 13:30 hrs., CDT 4/22/93. Recovered 200 sx excess cement. WOC 24 hrs.
Make cutoff & weld on wellhead. NU BOP's & test casing to 1500 psi.

J. Lara
Jun 16 1993

14. I hereby certify that the foregoing is true and correct

Signed Barratt L. Smith Title Sr. Operations Engineer

Date May 12, 1993

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side