

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1. TYPE OF WELL: ☒ OIL WELL ☐ GAS WELL ☐ DRY ☐ Other OCT 13 9 45 AM '93

2. TYPE OF COMPLETION:

☒ NEW WELL ☐ WORK OVER ☐ REPERFORATE ☐ PLUG BACK ☐ DIFF. REMOVAL ☐ Other OV

3. NAME OF OPERATOR

Devon Energy Corporation (Nevada)

4. ADDRESS AND TELEPHONE NO.

(405) 552-4511
20 North Broadway Suite 1500 Oklahoma City, OK 73102

5. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1982' FSL & 660' FWL

At top prod. interval reported below same

At total depth same

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR

Eddy County

13. STATE

NM

15. DATE SPUDDED

8/30/93

16. DATE T.D. REACHED

9/11/93

17. DATE COMPL. (Ready to prod.)

9/27/93

18. ELEVATIONS (OF, BKB, RT, OR, ETC.)*

3496.6'

19. ELEV. CASINGHEAD

3496.6'

20. TOTAL DEPTH, MD & TVD

8400'

21. PLUG, BACK T.D., MD & TVD

8356'

22. IF MULTIPLE COMPL.,

HOW MANY*

23. INTERVALS

DRILLED BY

ROTARY TOOLS

X

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

8045' - 8228', Lower Brushy Canyon

25. WAS DIRECTIONAL

SURVEY MADE

yes—enclosed

26. TYPE ELECTRIC AND OTHER LOGS RUN

CBL, DLL/MLL/GR, ZDL/CN/GR

27. WAS WELL CORED

no

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
13 3/8"	48#	872'	17 1/2"	700 sx - circ to surface	none
8 5/8"	32#	4353'	11"	1650 sx-circ to surface	none
5 1/2"	15.5 & 17#	8400'	7 7/8"	1100 sx - TOC = 2500'	none

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	7899'	7899'

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

8045' - 8228', 25 holes, 4" casing gun

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
8045' - 8228'	1500 gals 7 1/2% NEFE acid
	58,450 gals gelled 2% KCl
	water + 186,500# 16/30 sand

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
9/27/93		flowing				producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BSL.	GAS—MCF.	WATER—BSL.	GAS-OIL RATIO
10/11/93	24	16/64"	→	99	143	77	1444:1
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BSL.	GAS—MCF.	WATER—BSL.	OIL GRAVITY-API (CORR.)	
300#		→	99	143	77		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

sold effective 9/27/93

TEST WITNESSED BY

Dan Talley

35. LIST OF ATTACHMENTS

logs and inclination record

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Charles W. Horsman
District Engineer

DATE October 13, 1993

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recovered):

38.

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE
						VERT. DEPTH
				Rustler	1140'	1140'
				Base Salado	4240'	4240'
				Lamar	4474'	4474'
				Cherry Canyon	5630'	5630'
				Brushy Canyon	7006'	7006'
				Bone Springs	8286'	8286'

WELL NAME & NUMBER T 25-L Fed #12

LOCATION Section 25, T-23-S, R-31-E Eddy Co., NM
(Give Unit, Section, Township and Range)

OPERATOR Devon Energy, 20-North Broadway, Suite 1500, Oklahoma City, Oklahoma 73102-8260

DRILLING CONTRACTOR Nabors Drilling USA, Inc., 500 W. Wall, Suite 280, Midland, Tx 79701

The undersigned hereby certifies that he is an authorized representative of the drilling contractor who drilled the above-described well and that he has conducted deviation tests and obtained the following results:

DEGREES @ DEPTH	DEGREES @ DEPTH	DEGREES @ DEPTH	DEGREES @ DEPTH
0.75 409	0.50 6370		
1.00 872	0.75 6870		
1.25 1358	1.00 7376		
1.00 1797	1.25 7670		
1.00 2300	1.00 8230		
2.75 2800	2.00 8400		
3.00 2960			
2.25 3081			
1.25 3364			
0.50 3650			
1.00 3980			
2.50 4353			
1.00 4830			
0.50 5330			
0.50 5900			

Drilling Contractor Nabors Drilling USA, Inc.

By [Signature]
L. V. Bohannon, Drilling Supt.

Subscribed and sworn to before me this 22 day of August, 19 2001

[Signature]
Notary Public

My Commission Expires _____

Midland County Tx

