Form 3160-3 (November 1983) (formerly 9-331C)

(Other instructions on reverse side) **UNITED STATES**

SUBMIT IN TRIPLICATE*

Form approved.
Budget Bureau No. 1004—0136
Expires August 31, 1985

DEPARTMENT	<u> </u>	5. LEASE DESIGNATION AND SERIAL NO. NM-45235				
BUREAU OF						
APPLICATION FOR PERMITUT	O DRILL DE	PEN, OR PLUG B	ACK	6. IF INDIAN, ALLOTTE	OR TRIBE HAME	
TYPE OF WORK DRILL TIPE OF WELL	ECOMO 2	PLUG BACK []				
PELL X CAS OTHERDS		8. FARM OR LEASE HAND				
AME OF OPERATOR	/ AELEIV	/ ABUBIVED		Pure Gold C-17 Federal		
Santa Fe Energy Opera	ting Partners			9. WELL NO.		
550 W. Texas, Soite 1	92 N. Mar 21 - 1	APR 2	- 19 93	10. FIELD AND POOL.		
OCATION OF WELL (Beport location charles and				_•		
		17, T-23S, **31E		Sand Dunes, W 11. SSC., T., R., M., OR AND SURVEY OR AL	BLK.	
At proposed prod. sone	5)	Nush		Sec. 17, T-23S, R-31E		
DISTANCE IN MILES AND DIRECTION FROM NEAD	EEST TOWN OR POST OF			12. COUNTY OR PARISE	13. STATE	
18 miles East of Loving,	New Mexico			Eddy	NM	
DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT.	330'	3. NO. OF ACRES IN LEASE 480		ACREE ASSIGNED 40		
(Also to nearest drig, unit line, if any) DISTANCE FROM FROTORED LOCATIONS TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT.		9. PROPOSED DEPTH 8200	1	r or cashe tools Rotary		
ELEVATIONS (Show whether DF, RT, GE, etc.)	i		<u>!</u>	22. APPROX. DATE W	DEE WILL STARTS	
331 3' GR			June 15, 1			
	,	AND CEMENTING PROGRA	<u> → Secret</u>	OTY'S Potash /	+ 111-P Pet	
SIZE OF HOLE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	600 cv	to circulate		
17-1/2" 13-3/8" 12-1/4" 8-5/8"	48.0 32.0	4130'		sx to circulate		
7-7/8" 5-1/2"	15.50	8200'		e back to 4130 at least 39		
productive, 5-1/2" casing we plugged and abandoned in a programs as per Onshore Oil attachments: Drilling Program Exhibit A - Operations Exhibit B - BOP and Che Exhibit C - Drilling Be Exhibit D - Auxiliary Exhibit E - Topo Map of	manner consistant and Gas Orders of the Carlo Ca	er No. 1 are outli Exhibit F - Exhibit G -	l Regula ined in Plat Sh Well Si	tions. Specithe following owing Existing te Layout rations Plan	fic	
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If ne. If proposal is to drill or deepen direction eventer program, if any. SIGNED Laull Polats (This space for Federal or State office use)	nally, give pertinent o	or plug back, give data on lata on subsurface locations Sr. Drilling E	ngineer	DATE NOV	rember 19, 19	
				4.	75°05	
APPROVAL® SUBJECT TO ANY: GENERAL REQUIREMENTS AND	TITL			DATE		

SPECIAL STIPULATIONS
ATTACHED, and to NMOCD'S R-111- See Instructions On Reverse Side

PA GIL COMS. COmmISSION

Drawer DD Artesia, HM 88210

Form 3160-5 (June 1990)

UNITED STATES A DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004–0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-45235

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian. Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE Type of Well 8. Well Name and No. X Oil Well Other Pure Gold C-17 Fed #14 Name of Operator 9. API Well No. Santa Fe Energy Operating Partners, L.P. Not yet assigned Andress and Telephone No 10. Field and Pool, or Exploratory Area 550 W. Texas, Suite 1330, Midland, TX 79701 (915) 687-3551 Sand Dunes, West (Delaware 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State (L), 1780' FSL and 530' FWL, Sec. 17, T-23S, R-31E Eddy County, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment XX Notice of Intent New Construction Recompletion Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Other Change location Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Per recommendation by the BLM for topographic reasons, we respectfully request that the proposed drilling location for the subject well be changed to: (L), 1780' FSL and 530' FWL, Sec. 17, T-23S, R-31E Original application to drill was submitted on November 19, 1992. 1 1993 January 28, 1993 Sr. Production Clerk (This space for Federal or State office use) Approved by Conditions of approval, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

DISTRICT I P. O. Box 1980 Hobbs, NM 88240

DISTRICT II P. O. Drawer DD Artesia, NM 88210

OIL CONSERVATION DIVISION P. O. Box 2088 Santa Fe, New Mexico 87504-2088

DISTRICT III WELL LOCATION AND ACREAGE DEDICATION PLAT 1000 Rio Brazos Rd All distances must be from the outer boundaries of the section. Aztec, NM 87410 Well No. Lease Operator PURE GOLD 'C-17' 14 SANTA FE ENERGY OPER. PARTNERS, L.P. County Range Township. Unit Letter Section 31 EAST, N.M.P.M. **EDDY** 23 SOUTH L Actual Pootage Location of Well WEST feet from the 530 line and SOUTH 1780 feet from the Ground Level Elev. Producing Formation Pool 40 Sand Dunes, West (Delaware) Acres Delaware 3313' 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interest of all the owners been consolidated by communitization, unitization, forced-pooling, etc.?

Yes No If answer is "yes", type of consolidation the reverse side of this form if neccessary.) No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interest, has been approved by the division. OPERATOR CERTIFICATION I hereby certify that the information herein is true and complete to the best of my knowledge and belief. Signature Danel Printed Name Darrell Roberts Position Sr. Drilling Engineer Company Santa Fe Energy Operating Partners, L.P. Date January 28, 1993 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or W. BUSBA under my supervision, and that 530 the same is true and correct to the best of my knowledge and belief. Date Surveyed JANUARY 21, 1993 Signature and Seal of Professional Surveyor 1780' PROPESS TON Certificate No. R.P.S. #11398 LARRY W. BUSBY V.H.B. 500 ۵ JOB NO. 94022 1000 990 1320 1650 1980 2310 2640 2000 1500 330

DRILLING PROGRAM

SANTA FE ENERGY OPERATING PARTNERS, L.P. Pure Gold C-17 Federal No. 14

In conjunction with Form 3160-3, Application to Drill the subject well, Santa Fe Energy Operating Partners, L.P., submits the following ten items of pertinent information in accordance with Onshore Oil & Gas Order No. 10.

1. Geologic Name of Surface Formation: Alluvium

2. Estimated Tops of Significant Geologic Markers:

750'
3840'
4170'
5070'
7790'
8060'
8200'

3. The estimated depths at which water, oil, or gas formations are expected:

Water None expected in area
Oil Delaware Sand @ 4170'

Oil Lower Brushy Canyon @ 7790'

- 4. Proposed Casing Program: See Form 3160-3 and Exhibit A.
- 5. Pressure Control Equipment: See Exhibit B.
- 6. Drilling Fluid Program: See Exhibit C.
- 7. Auxiliary Equipment: A mud logging unit will be utilized to monitor penetration rate and hydrocarbon shows while drilling below the intermediate casing at 4100'.
- 8. Testing, Logging and Coring Program:

Drill Stem Tests: (all DST's to be justified on the basis of a valid show of oil or gas):

Ramsey Sand 4170'-4300' Lower Brushy Canyon 7790'-7900'

DRILLING PROGRAM

Pure Gold C-17 Federal No. 14 Page 2

Logging:

Dual Laterolog w/MSFL and Gamma Ray 4100'-8200' Compensated Neutron/Litho-Density/Gamma Ray 4100'-8200' Compensated Neutron/Gamma Ray (thru csg) Surface-4100'

Coring: No conventional cores are planned.

9. Abnormal Conditions, Pressures, Temperatures, & Potential Hazards:

No abnormal pressures or temperatures are anticipated. The estimated bottom hole temperature is 135 °F and the estimated bottom hole pressure is 3500 psi. No Hydrogen Sulfide or other hazardous gases or fluids have been encountered, reported or are known to exist at this depth in this area. No major lost circulation zones have been reported in the offsetting wells.

10. Anticipated Starting Date and Duration of Operations:

Road and location work will not begin until approval has been received from the BLM. The anticipated spud date is June 15, 1993. Once spudded, the drilling operation should be completed in approximately 16 days. If the well is productive, an additional 30 days will be required for completion and testing before permanent facilities are installed.


SANTA FE ENERGY OPERATING PARTNERS,L.P. OPERATIONS PLAN

Pure Gold C-17 Federal No. 14

- 1. Drill a 17 1/2" hole to approximately 600'.
- 2. Run 13 3/8" 48.0 ppf H-40 ST&C casing. Cement with 600 sx Class "C" cement containing 2% CaCl₂. Run centralizers on every other joint above the shoe. Apply thread lock to bottom two joints and guide shoe.
- 3. Wait on cement four hours prior to cutting off.
- 4. Nipple up a annular BOP system and test casing to 600 psi.
- 5. Drill a 12 1/4" hole to approximately 4130'.
- 6. Run 8 5/8" 32.0 ppf K-55 ST&C casing. Cement with 1750 sx Cl "C" Lite containing 12 pps salt and 1/4 pps celloflake followed by 250 sx Class "C" with 2% CaCl₂. Run guide shoe on bottom and float collar two joints of bottom. Centralize every other joint for bottom 400' of casing and place two centralizers in surface casing. Thread lock bottom 2 joints.
- 7. Wait on cement for six hours prior to cutting off.
- 8. Nipple up and install a 3000 psi. Double Ram and Annular BOP system with choke manifold.
- 9. Test BOP system to 3000 psi. Test casing to 1500 psi.
- 10. Drill 7 7/8" hole to 8200'. Run logs.
- 11. Either run and cement 5 1/2" 15.50 ppf K-55 LT&C casing or plug and abandon as per BLM requirements.

Exhibit A
Santa Fe Energy Operating Partners, L.P.
Pure Gold C-17 Federal No. 14
Section 17, T-23S, R-31E
Eddy County, New Mexico

DDR:PGC1714



SANTA FE ENERGY OPERATING PARTNERS, LP Pure Gold C-17 Federal No. 14
1480' FSL and 530' FWL
Sec.17, T23S, R31E
Eddy Co., New Mexico

TO PIT AND/OR MUD/GAS SEPARATOR

Z NOMINAL

REMOTELY OPERATED OR ADJUSTABLE CHOKE

PROPOSED DRILLING FLUID PROGRAM

0 - 600'

Spud mud consisting of fresh water gel flocculated with Lime. Use ground paper for seepage control and to sweep the hole. MW-8.5 ppg and Vis-40.

600-4130'

Drill out with brine water circulating the inner portion of the reserve pit. Utilize ground paper mixed in prehydrated fresh gel to sweep the hole. MW-10.0 ppg and Vis-28.

4130-8200'

Drill out with cut brine (30,000 ppm chlorides minimum) circulating the outer portion of the reserve pit. Maintain pH at 8.5-9.5 with caustic and sweep the hole as necessary with ground paper. If it becomes necessary to mud up due to hole conditions, utilize a cut brine/Drispac system for 15-20 WL and a Vis of 30-32. MW-8.5/8.9 ppg.

Exhibit C
Santa Fe Energy Operating Partners, L.P.
Pure Gold C-17 Federal No. 14
Section 17, T-23S, R-31E
Eddy County, New Mexico

DDR:PGC1714

AUXILIARY EQUIPMENT

DRAWWORKS BDW 650M 650 HP, with Parmac Hydromatic brake

ENGINES Two Caterpillar D-353 diesels rated at 425 HP each

ROTARY Ideco 23", 300 ton capacity

MAST/SUB Ideal 132',550,000 lb rated static hook load with 10 line

Wagner 15' high substructure

TRAVELLING Gardner-Denver, 300 ton, 5 sheave w/ BJ 250 ton hook.

EQUIPMENT Brewster Model 7 SX 300 ton swivel.

PUMPS Continental-EMSCO DC-700 and DB-550, 5 1/2 X 16" Duplex, Compound

driven.

PIT SYSTEM 1-Shale Pit 6X7X35',1-Settling Pit 6X7X38', 1-Suction Pit 6X7X34' w/5 mud

agitators. Two centrifugal mud mixing pumps and a Double Screen Shale

Shaker.

LIGHT Two CAT 3306 diesel electric sets 180 KW prime power.

PLANT

BOP 13 5/8" 5000 psi WP double ram and 13 5/8" 5000 psi WP Shaffer Annular

EQUIP Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon

closing unit.

Exhibit D

Santa Fe Energy Operating Partners, L.P.

Pure Gold C-17 Federal No. 14

Section 17, T-23S, R-31E Eddy County, New Mexico

DDR:PGC1714

LOCATION & ELEVATION VERIFICATION MAP





EXHIBIT E

SANTA FE ENERGY OPERATING PARTNERS, LP Pure Gold C-17 Federal No. 14 1980' FSL and 330' FWL Sec 17, T23S,R31E Eddy Co., New Mexico

. Сес sun ons нви 02953	85.821 H R N	1	i .		-	W.F.
32933	82	ā0.33 I [†]	.1 \ \ Gov*t."			MIDLAND WA
<u>: </u>	Beico	<u> </u>	915.	31.5	2.5.	2.5.
Pichardson Oi-s HBU 82952	(Richardson & Bass) E-5229	Conoco HBU 02953	Gule Flag-Redfern 3 21-77 K 6008 K 6777 K 6008 Z 743	Guiff 12∵ : 83 1966	M P Grace 9-1-73 0431054	Sente Fe Ener 12 Mignett Ener 847 25 2709
35	36	31	32	7.1	74	: :
dson Oils g P	5 Shell 1 5 5 7 2 9	RichardsonOils #80	!	33	34 S M.P. Grant	35
1952	PR Gass (Shell) Shell) Aroso Osse State Organisation	0 19 53			Grace - Joston Baby - Fea 10 43-75 114 - 127 74 NTO 6700	"D. Ross
130 23 2 40 J3	Conoco (Richardson Oli)	46 45 4/39.92 3/39.94 2/39.98	25 98	9.5. 19.75 499.74 3139.74 2139.71	25.51 4935.55 3135.52 2135.45	U ¹ S
1125	MBU 02884 52884 Shift character argi:	HBU Bass Ent.	Send of the send o	(Yates Pet etai)	Yates Pet. etal Santa Fe Enar. /a Milotell Ener	Mobil **
	Beico 3 Bass Em 300	Bevo Ent (1997) O'R Boss) (America) Common Men un (1997) O'R Boss) O'R Common O'R (1997)	Richards (HBD) 9 1 94 9 1 94 9 1 97 9 1 97 1 8973 HBU MP Grace	Sonto Fe Ener., /4 (Mitchell Ener, etc). /4) 5 - 1 - 94	ercal/s4 91953 202	T A-30S
2	(1543280	Richardson Oil 6 PROLEMINATION	Heu MP Grace 02803 5 Capin Boby Fed	2 22	3	2
1	-wos ⊕(6 smil) ∃e cc =et	Thru Line etal)	02803 5 Caan Booy Fea 104:50 T/4:4 8:75	•	i	_
ļ	allMorr Disch	21.9 -1	1		SAND DUI	WES,NO. 537
***	Hudson - Fed." 1 5-10-00 18Ms Sec. 18Ms	James Rch.		⊚ [†] **P\$ • Fed." U.\$.	ļ	Mor
Mobil 14		d' id Senaferem	Richardson Oil		J. S.	State
0546625	Shell 5 · 1 · 74 0546732	21861 WOCAR CHI	8 1-6112) Santa Fe 271988 Ener (Military Ener.)	Santa Fe Ener Mitchell Ener,	Santa Fe Ener, Santa Fe Ener. Mitchell Ener, 1 1 36 etal 12 85926	Marathon etc
Phillips 6 - (- 74 2'841		18-chardser Oil	* etal./2)	etcil/2 9 · l · 93 77006 65.55	91 99 A00 99 77046 A00 99	04044
1	12	7 T YF 7	91 77046 66 92 8	9		Union Bancia 11 7015400
0546625		P.R. Bass, etal :	⊚ 8Hr		Santa Santa Fe Ener.	Max Wilson
Phillips	•	6 1 9 6 7 Boss Ent. James 7 James 7 700.	TDIA.921 9.1Mil. "No.Pure		85926 8101.72 400 22 7704 93 55 22 5990 6590	Bauerdo-f
21641	U. 3.		Gold-Feel." Alt. Jorney Meh. US.	u.s.	#8P	24 25 25 e3 U 5
Phillips 5 · I · 74 0532769	Phillips HBP 0532516	4: 42 P.R. Bose, erol	Santa Fe Ener. Sunto Fe Ener. (Page)	Yates Pert.	Devon Ener: HBP	Devon Ener.
1 .		02887 2145 2 ⁴	d.:sea Terro Res.)	V-120	0405444	4 · 1 74 0533177
4	181 13		1 2.c	1780	CH.	нес
1	,5	Shell 21 Bass eros	⁷ نت حت ا	3.7 Mil	15	(Marathon)
1	!	9.1.74 Shell 0546132 6: 74	0	El Pasa Nat Gas)		Tex Amer.) (14-1 Devan Er Todd-Fed. Devan Er Obuse : Lien Disc. 0404441 Sil. Dr
1		Phillips 1		(Afoke Disc.)		6.7 Mi) 541.077 TD(6.558
Phillips	Ostivi	5 - 1 - 74 + 216 39 U.S. 4/ 55 - 1 Kath.C.	PROPOSED " LOCATION	(C 8-15-71) State 23		Us
H8P 3 532516	0532516	4155 1	Maiser- Francis	(Paga)	Tex. Amerit Marathon HBP	Devon Ener
Phillips	Songy Unit T	7/ 50 54 LD 34 6237L	38463	38464 Kaiser Francis	0405444	0405444
3 10-17-41	83 1.4 AAA	E! Poso Expl. 5 : 1 74 21539		Qit & Gas		
9s.	Phillips 5 74	ansı ji 19	20	21	22	23
	0532341 51 Page Nich			128 ⊨	Potesi Muse Fee	(Pra) (Osati road) (Merrial Merrial Ameria
.	2 007	2'65' Z' El Paso Espl. 2155'' Phillips 4: 1:74: 0533177	Pure Gold-Fed." \$ 1-8	**************************************	Muge-Fea. TD 43&2 074 6: 2: 62	Todd-Fed
	8.5. I	. ea	U.S. 3.1 Mil.	Pure Gold - Fed.	и.\$.	U.S. P40
Phitlips HBP 0546316		Phillips 4 : 1 : 74	Phillips (Mobil)		Marathon HBP	Marathoni (Marathan 0418720 Per
. 3.6.376		0533177 3-13 I ^t E1 Pasa Expl. 21 %	2545 035 - 078487 El Pasa Expi 21 % Paga	Pogo 40859	0418220 Devon Ener.	tobase of Sil-Devi
6	25	SAND DINE	i 1/1/2 1	Page Page	to base of Sil.Dev.	Tex. Amer. Of (80)
234	Vales	1171- 1130	29 (El Pasa Not.)	Pogo Prod. Pure: Gold Fed. 28 Br. Cany, Disc.	Farell in	TO 6048 26 ATOROL
:77	10-17-91 3 46.	H · 6 · 75 21840	[D]4690	Sand Dunes	Ai Wrigh.	Devon Ener: P47
ŀ	1,	i,	3-1-64 (3)1	Fed. TO 150\$7 \$\AS-10-90	TD 43366 Del-1267 C/A 5 20 -61	Todd-Fed
<u>, </u>	' ₄₁ ' <i>U. S.</i>	. v.5.	CCBSE I II C "Mobil-Form"	" · ·	U.S.	11 5

EXHIBIT F

SANTA FE ENERGY OPERATING PARTNERS, LP Pure Gold C-17 Federal No. 14 1980' FSL and 330' FWL Sec. 17, T23S, R31E Eddy Co., New Mexico



MULTI-POINT SURFACE USE AND OPERATIONS PLAN SANTA FE ENERGY OPERATING PARTNERS, L.P.

Pure Gold C-17 Federal No. 14 1980' FSL & 330' FWL Section 17, T-23S, R-31E Eddy County, New Mexico

This plan is submitted with Form 3160-3, Application for Permit to Drill, covering the above described well. The purpose of this plan is to describe the location of the proposed well, the proposed construction activities and operations plan, the magnitude of necessary surface disturbance involved, and the procedures to be followed by rehabilitating the surface after completion of the operations, so that a complete appraisal can be made of the environmental effects associated with the operation.

1. EXISTING ROADS.

A. Exhibit E is a 15 minute topographic map which shows location of the proposed wellsite and roads in the vicinity. The proposed location is situated approximately 18 miles northeast of Loving, New Mexico.

DIRECTIONS:

1. From the intersection of State Highway 128 and the Lea/Eddy County line, go northwest 6.5 miles on State Highway 128 to a point 330' from location.

2. PLANNED ACCESS ROAD.

A 14' wide access road will extend from State Highway 128 approximately 16' west of the location.

3. LOCATION OF EXISTING WELLS.

A. The well Locations in the vicinity of the proposed well are shown Exhibits E & F.

4. LOCATION OF EXISTING AND/ OR PROPOSED FACILITIES.

- A. There are two existing producing gas wells on this lease at this time.
- B. In the event the well is productive, the necessary production equipment will be installed on the drilling pad. If the well is productive of oil, a gas or diesel self-contained unit will be used to the necessary power.

Multi-Point Surface Use and Operations Plan

Pure Gold C-17 Federal No. 14

Page 2

5. LOCATION AND TYPE OF WATER SUPPLY

A. It is planned to drill the well with both fresh water and brine water systems. Both types of waters will be hauled to the location by truck over existing roads. Both types will be obtained from commercial sources.

6. SOURCES OF CONSTRUCTION MATERIALS.

A. Any caliche required for construction of the drilling pad will be obtained from a pit located of the wellsite.

7. METHODS OF HANDLING WASTE DISPOSAL

- A. Drill cuttings will be disposed of in the reserve pits.
- B. Drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry.
- C. Water produced during operations will be either placed in the reserve pits and allowed to evaporate or collected in tanks until hauled to an approved disposal system or a separate disposal application will be submitted to the BLM for appropriate approval.
- D. Oil produced during operations will be stored in tanks until sold.
- E. Human waste will be disposed of per current standards.
- F. Trash, waste paper, garbage, and junk will be collected in trash trailers and disposed of in an approved waste facility such as a land fill. The trash trailers contain all of the material to prevent scattering by the wind.
- G. All debris will be removed from the wellsite within 30 days after finishing drilling and/or completion operations.

8. ANCILLARY FACILITIES.

None required

9. WELLSITE LAYOUT

A. Exhibit G shows the dimensions of the well pad and reserve pits, and the location of major rig components.

Multi-Point Surface Use and Operations Plan

Pure Gold C-17 Federal No. 14 Page 3

- B. The ground surface of the location is located among several sand dunes with vegetation growing on them. The location will constructed by leveling the necessary dune and covering the sand with at least six inches of compacted caliche.
- C. The reserve pits will be plastic lined.
- D. A 400' X 400' work area which will contain the pad and pit area has been staked and flagged.

10. PLAN FOR RESTORATION OF THE SURFACE.

- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleared of all trash and junk, to leave the wellsite in as aesthetically pleasing a condition as possible.
- B. Unguarded pits, if any, containing fluid will be fenced until they have been filled.
- C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the Bureau of Land Management and the United States Geological Survey will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and levelled within 300 days after abandonment.

11. TOPOGRAPHY

- A. The wellsite and access route are located in a relatively flat area.
- B. The top soil at the wellsite is sandy.
- C. The vegetation cover at the wellsite is moderately sparse, with prairie grasses, some mesquite bushes, and shinnery oak.
- D. No wildlife was observed but it is likely that deer, rabbits, coyotes, and rodents traverse the area.
- E. There are no ponds, lakes, streams, or rivers within one mile of the wellsite.
- F. There is no evidence of any archaeological, historical, or cultural sites in the vicinity of the location.

Multi-Point Surface Use and Operations Plan

Pure Gold C-17 Federal No. 14 Page 4

12. OPERATOR'S REPRESENTATIVES.

A. The field representatives responsible for assuring compliance with the approved surface use plan are:

Darrell Roberts Michael R. Burton Division Operations Manager Senior Drilling Engineer Santa Fe Energy Operating Santa Fe Energy Operating Partners, L.P. Partners, L.P. 550 W. Texas, Suite 1330 550 W. Texas, Suite 1330 Midland, Texas 79701 Midland, Texas 79701 915-686-6614 - office 915-686-6616 - office 915-699-1260 - home 915-684-4130 - home 915-559-6842 - cellular 915-553-1214 - cellular

13. CERTIFICATION

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Santa Fe Energy Operating Partners, L.P., and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.

SIGNED this _______ day of November, 1992. _______ Darrell Roberts, Senior Drilling Engineer

/tjm PGC1714