

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7040

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 380' FEL, Sec. 35, T23S, R3E

5. Lease Designation and Serial No.

NM-19199

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cal-Mon No. 19

9. API Well No.

30-015-27496

10. Field and Pool, or Exploratory Area

Undes Ingle Wells Delaware

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other TD & Prod casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 8400'. TD reached @ 1145 hrs CDT 10-4-93. Logged well with Western Atlas. Ran 196 jts 5-1/2", 15.5# & 17#, J-55 & N-80, LT&C casing. Float shoe @ 8400'. Float collar @ 8355'. Stage tools @ 4114' & 6000'. Howco cemented 1st stage with 140 sx Halliburton Lite @ 12.4 ppg followed by 500 sx Premium Plus @ 13.6 ppg. Bump plug. Float held. Drop bomb & open DV tool @ 6000'. Circulate 5 hrs between stages. Recover 121 sx excess cement. Cement 2nd stage with 475 sx Halliburton Lite @ 12.4 ppg followed by 100 sx Premium Plus @ 14.8 ppg. Bump plug. Float held. Drop bomb & open DV tool @ 4114'. Circulate 5 hrs between stages. Recover 114 sx excess cement. Cement 3rd stage with 440 sx Halliburton Lite @ 12.4 ppg followed by 50 sx Premium Plus Neat @ 14.8 ppg. Plug down close DV tool @ 4114' 0415 hrs CDT 10-6-93. Recovered 10 sx excess cement. Set slips and make cut-off. ND BOP's and weld on casing head. Test to 2500 psi.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Senior Operations Engineer

Date

October 21, 1993

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Nov 19 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

CARLSBAD, NEW MEXICO