

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED
SEP 10 1993

Form C-105
Revised 1-1-89

WELL API NO.
30-015-27510

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
K-6600

7. Lease Name or Unit Agreement Name

Nash Unit

8. Well No.

#14

9. Pool name or Wildcat

Nash Draw Brushy Canyon

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

b. Type of Completion:
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DEEP RESVR ☐ OTHER ☐

2. Name of Operator
Strata Production Company

3. Address of Operator
P.O. Box 1030, Roswell, New Mexico 88202-1030

4. Well Location
Unit Letter A: 660 Feet From The North Line and 500 Feet From The East Line
Section 13 Township 23 South Range 29 East NMPM Eddy County

10. Date Spudded
7/3/93

11. Date T.D. Reached
7/14/93

12. Date Compl. (Ready to Prod.)
8/1/93

13. Elevations (DF & RKB, RT, GR, etc.)
3004' GR

14. Elev. Casinghead

15. Total Depth
7280'

16. Plug Back T.D.
7268'

17. If Multiple Compl. How Many Zones?
N/A

18. Intervals Drilled By
Rotary Tools Grace, Cable Tools
0'-7280'

20. Was Directional Survey Made
Yes

19. Producing Interval(s), of this completion - Top, Bottom, Name
6870'-6889' Brushy Canyon Delaware

21. Type Electric and Other Logs Run
CNL; DLL/MSFL; CBL; CAL; PCR

22. Was Well Cored
Sidewall

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8"	48#	315'	17 1/2"	400 sx Premium Plus	85 sacks
8 5/8"	32#	3045'	12 1/4"	1075 sx 35/65 Poz C; 200 sx Class "C"	200 sacks
5 1/2"	17#	7280'	7 7/8"	670 sx 50/50 Poz H; 295 sx 35/65 Poz C; 100 sx Class H	303 sacks

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	6788'	6788'

26. Perforation record (interval, size, and number)
6870' - 6889' (15) .42 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
6870'-6889'	Acidize w/1400 gal 7 1/2% NEFE; Frac w/YF135 gal & 47900# 16/30 Super Sand

28. PRODUCTION

28.		Production Method (Flowing, gas lift, pumping - Size and type pump)					Well Status (Prod. or Shut-in)	
Date First Production		Flowing					Producing	
8/2/93								
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio	
8/6/93	24	21/64		300	143	197	477/1	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)		
680#	-0-		300	143	197	39.3		
						Test Witnessed By		

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
Sold

30. List Attachments

CNL; DLL/MSFL; Deviation Survey

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Carol J. Garcia Printed Name Carol J. Garcia Title Production Records Manager Date 9/2/93

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt 307'
B. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres _____
T. Glorieta _____
T. Paddock _____
T. Blinebry _____
T. Tubb _____
T. Drinkard _____
T. Abo _____
T. Wolfcamp _____
T. Penn _____
T. Cisco (Bough C) _____

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand 3190'
T. Bone Springs 6948'
T. _____
T. _____
T. _____
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
No. 2, from _____ to _____
No. 3, from _____ to _____
No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
Surface	307'	307	Rustler				
307'	1786'	1479	Salado				
1786'	3190'	1404	Castille				
3190'	4293'	1103	Top of Bell Canyon				
4293'	5278'	985	Cherry Canyon				
5278'	6948'	1670	Brushy Canyon				
6948'	7280'	332	Bone Spring				